## **Tooling**

## PATRIOT® 6 Ton, Scissor Action

Hydraulic Self-Contained, 18V Lithium-Ion

**Tool Series:** PAT500SJ

- Interchangeable scissor action crimping and cutting jaws
- 180° head rotation
- Uses W and X style dies
- Ergonomically balanced tool design
- Includes 2 batteries, charger, and polymer carrying case
- EP Enhanced Power tools accept 2.0, 3.0, 4.0, 5.0, and 6.0Ah
   Makita batteries



Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, and Compact Conductors

Taps:

Copper: #10 sol. to 2/0 str.

Aluminum & ACSR: #14 sol. to 4/0 ACSR

Stirrups:

#6 to 4/0 ACSR

Overhead Full Tension Deadends, Full Tension Splices and

Terminals:

#10 str. to 4/0 ACSR

Installs Splices, Taps or Terminations:

#8 to 500 kcmil Copper Stranded (YA, YA-L, YS, YS-L)

#8 to 350 kcmil Copper Flex

#8 to 350 kcmil Aluminum (YA-A, YS-A)

Interchangeable Jaw Assemblies:

PATMD6LWJAW Crimp jaw with BG and D3 grooves
PATMD68LWJAW Crimp jaw with O and D3 grooves
PATMD66LWJAW Crimp jaw with D3 groove only
PATMDXPJLWJAW Crimp jaw with X, P & J grooves
PATMD430LWJAW Crimp jaw, Dieless, #4 AWG - 3/0 AWG

PATMDCUTLWJAW
PATMDCUTCLWJAW
PATMDCUTGLWJAW

Accessories:

BAT18VLI: 3.0Ah Li-Ion battery
BAT18V5AHLI: 5.0Ah Li-Ion battery
PATCHGRLI: 120V-AC Charger
PATCHGRLIDC: 12/24V-DC Charger

**PATMD6LWJWCVR:** Jaw covers for PATMD6 and PATMD68 versions **PATMD66LWJWCVR:** Jaw covers for PATMD66 snub-nose versions

PT10074020: Wrist strap

W28K: Cutter Dies (cuts 4-4/0 Cu, Al, ACSR)

**WDIETREE:** W-die holder for 6 die sets



Models:

 PAT500SJ6LI
 BG and D3 grooves (3.0Ah)

 PAT500SJ68LI
 O and D3 grooves (3.0Ah)

 PAT500SJ66LI
 D3 groove only (snub-nose) (3.0Ah)

 PAT500SJ6L5
 BG and D3 grooves (5.0Ah)

 PAT500SJ68L5
 O and D3 grooves (5.0Ah)

 PAT500SJ66L5
 D3 groove only (snub-nose) (5.0Ah)

Crimp/Cut Kits:

 $\textbf{PAT500SJ6LICUTKIT1} \qquad \text{Kit includes crimp head with BG \& D3 grooves,} \\$ 

cutter jaw with ACSR blades, 120V charger and

2 batteries (3.0Ah)

PAT500SJ68LICUTKIT1 Kit includes crimp head with O & D3 grooves,

cutter jaw with ACSR blades, 120V charger and

2 batteries (3.0Ah)

Specifications:

Output Force: 6 Tons

Tool Weight: 10.10 lbs (without battery)
Size: 17.00" X 14.25" X 3.00"
Die Style: W and X (with crimping jaws)
Operating Voltage: 18 V-DC Lithium-lon
Recharge Time: 30 minutes (3.0Ah)

30 minutes (3.0Ah) 45 minutes (5.0Ah)

Warranty: 5 year limited warranty

Lifetime warranty on INFINITY DRIVE® 3 year on batteries and charger



