

TC26^{ex}-NI Accessories

Datasheet











Accessories for use in hazardous areas

Accessories are approved for:

- UL: Class I,II, III Div 2 (E321557)



Standard battery	
Description	 certified in combination with TC26^{ex}-NI
	 Lithium-ion battery 3.85 V/3400 mAh (13.09 Wh)
	May only be changed and charged outside hazardous areas!
Order no.	B7-A2Z0-0075



Extended battery	
Description	- certified in combination with TC26ex-NI
	 Lithium-ion battery 3.85 V/5260 mAh (20.25 Wh)
	May only be changed and charged outside hazardous areas!
Order no.	B7-A2Z0-0080




Hand strap	
Description	- certified in combination with TC26ex-NI
	- only for Touch Computer without scan handle
Order no.	B7-A2Z0-0079



Scan handle

Description	- certified in combination with TC26ex-NI
	 simple assembly and disassembly without tools
	 does not block camera or other feature
	 only usable without hand strap
	- charging with mounted scan handle possible
	May only be changed outside hazardous areas!
Order no.	B7-A2Z0-0078



Screen protector

Description	 Certified in combination with TC26^{ex}_NI 	
	- 1 piece	
	May only be changed outside hazardous areas!	
Order no.	B7-A2Z0-0076	



Stylus

Otytuo	
Description	- Suitable for TC26 ^{ex} -NI
	- passive stylus
	with spiral cable
	- 3 pieces
	May only be changed outside hazardous areas!
Order no.	17-S1Z0-0008

Accessories for use outside hazardous areas



4-slot battery	charging	station
Description	_	Charging fo

Description	 Charging four batteries 	
	 Charging Standard battery and Extended battery 	
	 Charging display via LED 	
Scope of delivery	4-slot battery charging station	
Also required	(not included with delivery)	
	 Power supply with DC connecting cable 	
	- AC power cable	
Order no.	G7-A0Z0-0054	



Base station

Description	- Charging the Touch Computer	
	 Communication via USB 	
Scope of delivery	Base station	
Also required	(Not included with delivery)	
	 Power supply with DC connecting cable 	
	 AC power cable 	
	 USB cable for data communication (03-9919-0013) 	
Order no.	G7-A0Z0-0052	



Power supply with DC connecting cable

Description	 for 4-slot battery charging station and Base station
	 Input voltage: AC 100 to 240 V
	- Output voltage: DC 12 V/4.16 A/50 W
Order no.	G7-A0Z0-0023



AC power cable

Description	- 3-wire	
	- country-specific	
Order no.	Version: US + Canada	G7-A0Z0-0024
	Version: EU + APAC	G7-A0Z0-0026
	Please purchase the required country-specific cables in the respective country!	



Wall Charger

Description	Input voltage: AC 100 to 240 VOutput voltage: DC 5 V/2.5 A/12.5 W	
Order no.	Version: US	G7-A0Z0-0056
	Version: EU	G7-A0Z0-0057
Also required	(Not included with delivery) - USB cable (G7-A0Z0-0046)	



USB cable

OOD Cable	
Description	 Connection between Mobile Computer and base station for data communication
	 USB (A) to micro USB (B)
	- Length: 1 m
Order no.	03-9919-0013



USB cable

USB Cable	
Description	 Connection between Touch Computer and PC for data communication
	 Connection between Touch Computer and Wall Charger for charging
	- USB (A) to USB (C)
	- Length: 1.5 m
Order no.	G7-A0Z0-0046
	