| SPECIFICATIONS | MW826ST | | | |
|---------------------------------------|---|---|---|--|
| Projection System | DLP® | | | |
| Native Resolution | WXGA, 1280x800(450 type) | | | |
| Brightness | 3400AL | | | |
| Contrast Ratio | 12000:1 | | | |
| Display Color | 1.07 Billion Colors | | | |
| Lens | F/#=2.6 ; f=6.9 mm | | | |
| Aspect Ratio | Native 16:10 (5 aspect ratio selectable) | | | |
| Throw Ratio | 0.49 | | | |
| Clear Image Size / Maximum Image Size | 70"~120" / 120" | | | |
| coom Ratio .amp Type | Fixed 200W | | | |
| amp Mode | | | | |
| Normal/Economic/SmartEco/LampSave) | 5000/10000/10000/15000 hours | | | |
| Keystone Adjustment | 1D, Vertical +/- 30 degrees | | | |
| Projection Offset | 105%±2.5% (Full-Height) | | | |
| Resolution Support | VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking" | | | |
| lorizontal Frequency | 15K~102KHz | KHz | | |
| ertical Scan Rate | 23~120Hz | | | |
| Compatibility | HDTV Compatibility | 480i, 480p, 576i, 567p, 7 | 20p, 1080i, 1080p | |
| | 3D Compatibility (Please refer to User's Manual for detailed support timing.)" | Frame Sequential: Up to 720p Frame Packing: Up to 24 Hz 1080p Side by Side Half: Up to 60Hz 1080p Top Bottom: Up to 60Hz 1080p | | |
| Interface | Computer in (D-sub 15pin) | x 2 (Share with compone | x 2 (Share with component) | |
| | Monitor out (D-sub 15pin) | x 1 | x 1 | |
| | Composite Video in (RCA) | x 1 | | |
| | S-Video in (Mini DIN 4pin) | x 1 | x 1 | |
| | HDMI | x2 (1 share with MHL) | | |
| | | | | |
| | Audio in (Mini Jack) | x2 | | |
| | Audio out (Mini Jack) | x 1 | | |
| | Audio L/R in (RCA) | x 1 | | |
| | Speaker | 10Wx 1 | | |
| | USB (Type A) | x1 (power only 5V/1.5A) | | |
| | USB (Type Mini B) | x1 (Download & page/down) | | |
| | RS232 (DB-9pin) | x 1 | | |
| | , | | | |
| | LAN (RJ45) | | x 1 | |
| Dimensions | Dimensions(W x H x D) | | 296 (W)*239(D)*120(H) mm | |
| | Weight | 2.6 Kg (5.7 lbs) | | |
| Power | Power Supply | | AC 100 to 240 V, 50/60 Hz | |
| | Power Consumption | 260W(typical), Standby< standby<2W | 260W(typical), Standby<0.5W, Network standby<2W | |
| udible Noise (Normal/Economic) | 33/29 dBA (Normal/Economic mode) | | | |
| Dn-Screen Display Languages | Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages) | | | |
| Picture Modes | Bright / Presentation / sRGB / Cinema | / (3D) / User 1 / User 2 | | |
| Accessories | Standard Optional | | | |
| | Remote Control w/ Battery RCE013, RCE013J (for J sku) | PointWrite | PW02 | |
| | Power Cord (by region) | FingerTouch | PT12 | |
| opposition | | | | |
| Accessories | User Manual CD | Spare Lamp Kit | 5J.JGP05.001 | |
| ccessories | User Manual CD Quick Start Guide | Spare Lamp Kit Wall Mount | 5J.JGP05.001 WM06G3 | |

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MW826ST Digital Projector

- SmartEco Power Saving Technology
- 0.49 Short Throw Ratio
- Designed for Education & IWB
- Blu-ray Full HD 3D support
- PointWrite Interactive Solution
 Compatible









Touchboards

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

BenQ America Corp. BenQ.us

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

