SPECIFICATIONS	MX825ST			
Projection System	DLP®			
Native Resolution	XGA(1024X768)			
Brightness	3300AL			
Contrast Ratio	12000:1			
Display Color	1.07 Billion Colors			
Lens	F/#=2.6 f=6.9mm			
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)			
Throw Ratio	0.61			
Clear Image Size / Maximum Image Size	60"~120" / 120" Fixed			
Zoom Ratio Lamp Type	200W			
Lamp Mode				
(Normal/Economic/SmartEco/LampSave)	5000/10000/10000/15000 hours			
Keystone Adjustment	1D, Vertical +/- 30 degrees			
Projection Offset	115%±2.5% (Full-Height)			
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x	/GA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking"		
Horizontal Frequency	15K~102KHz			
Vertical Scan Rate	23~120Hz			
Compatibility	HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p		
	3D Compatibility (Please refer to User's Manual for detailed support timing.)"	Frame Sequential: Up to 720p Frame Packing: Up to 24 Hz 1080p Side by Side Half: Up to 60Hz 1080p Top Bottom: Up to 60Hz 1080p		
Interface	Computer in (D-sub 15pin)	x 2 (Share with component)		
	Monitor out (D-sub 15pin)	x 1		
	Composite Video in (RCA)	x 1		
	S-Video in (Mini DIN 4pin)	x 1		
	HDMI	x2 (1 share with MHL)		
		x2		
	Audio in (Mini Jack)			
	Audio out (Mini Jack)	x 1		
	Audio L/R in (RCA)	x 1		
	Speaker	10Wx 1		
	USB (Type A)	x1 (power only 5V/1.5A)		
	USB (Type Mini B)	x1 (Download & page/down)		
	RS232 (DB-9pin)	x 1		
	LAN (RJ45)	x 1		
Dimensions	Dimensions(W x H x D)	296 (W)*239(D)*120(H) mm		
	Weight	2.6 Kg (5.7 lbs)		
Power	Power Supply	AC 100 to 240 V, 50/60 Hz		
	Power Consumption	260W(typical), Standby<0.5W, Network standby<2W		
Audible Noise (Normal/Economic)	33/29 dBA (Normal/Economic mode)	33/29 dBA (Normal/Economic mode)		
On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages)			
Picture Modes	Bright / Presentation / sRGB / Cinema / (3D) / User 1 / User 2			
Accessories	Standard Optional			
	Remote Control w/ Battery RCE013, RCE013J (for J sku)	PointWrite	PW02	
	Power Cord (by region)	FingerTouch	PT12	
	User Manual CD	Spare Lamp Kit	5J.JGP05.001	
	Quick Start Guide	Wall Mount	WM06G3	
	Warranty Card (by region)	Dust Filter	5J.JGV14.001	

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MX825ST

Digital Projector

- SmartEco Power Saving Technology
- 0.61 Short Throw Ratio
- Designed for Education & IWB
- Blu-ray Full HD 3D support
- PointWrite Interactive Solution Compatible











296mm -



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

