

IL01 43"/55"

Smart Interactive Signage



The **germ-resistant display** allows to safely interact on the touchscreen thanks to the nano ionic silver formula coating, which is 99.9% efficient against common germs (TÜV Rheinland certified).



With the **X-Sign Content Management** Software you can edit, manage and customise content with 150+ templates, and display it directly on the screen from a USB Drive.



Display content both in **portrait or landscape** mode, for a wide range of interactive signage applications thanks to the increased flexibility.



Combined with DMS Cloud and DMS Local, BenQ's **Device Management Solution** helps you easily manage all your BenQ displays at the same time.

MODEL		IL4301	IL5501	
Panel	Screen Size	43"	55"	
	Resolution	UHD 3840 x 2160	UHD 3840 x 2160	
	Brightness (Typ.)	400 nits	400 nits	
	Contrast Ratio (Typ.)	1200: 1	1300: 1	
	Viewing Angle (H/V)	178 degree (H) / 178 degree (V)	178 degree (H) / 178 degree (V)	
	Response Time (G-t-G, ms)	8	9	
	Backlight Life (hrs)	40,000	50,000	
	Panel Surface	AG, Haze 1%	AG, Haze 3%	
	Operating Hour	24 hrs / 7 days	24 hrs / 7 days	
Touch Solution	Orientation	Landscape / Portrait	Landscape / Portrait	
	Touch Technology	Infrared Touch	Infrared Touch	
	Touch Points	40	40	
Platform Solution	Resolution	32768 x 32768	32768 x 32768	
	System Memory	3GB	3GB	
	Storage	32GB	32GB	
	OS	Android 8.0	Android 8.0	
Power	Power Supply	100V~240V, 50-60Hz	100V~240V, 50-60Hz	
	Power Consumption	Maximum (W/h)	150	230
		Typical (W/h)	82	111
		Standby Mode (W/h)	<0.5W	<0.5W
	AC Power Switch	Yes	Yes	
	Wake Up	HDMI / LAN	HDMI / LAN	
Environment	Operation Temperature	0°C ~ 40°C	0°C ~ 40°C	
	Operating Humidity	20% ~ 85% RH Non-Condensing	20% ~ 85% RH Non-Condensing	
	Energy Efficiency	Energy 8.0 Certified	Energy 8.0 Certified	
Connectivity	Input	VGA / HDMI / Display Port	x 1 / 2.0 x 2 / 1.2 x 1	
	Output	HDMI	2.0 x 1	
	USB	Type A / Type B	2.0 x 2 / 2.0 x 1 (For Touch)	
	LAN		2.0 x 2 / 2.0 x 1 (For Touch)	
	Remote Controller	Yes	Yes	
	Internal Speaker	Yes	Yes	
Audio	Internal Speaker	10W x 2	10W x 2	
	Mechanical	Dimension (mm) Screen	1011.0 x 599.2 x 97.4	1284.1 x 754.9 x 92.6
		Weight (kg) Net Weight / Gross Weight	18.8 / 24.0	29.1 / 35.2
	Bezel Width (mm)	16.6 / 16.6 / 16.6 / 16.6	16.6 / 16.6 / 16.6 / 16.6	
	Wall Mounting (VESA) (Screw Type / Max. Length)	200 x 400 mm (4 holes); 4 x M6 x 8L	400 x 400 (4 holes); 4-M6 x 15L	
	OPS Slot	x 1	x 1	
Unique Software Support	Wireless Presentation	InstaShare	InstaShare	
	Media Content	X-Sign	X-Sign	
	Digital Broadcasting	X-Sign Broadcast	X-Sign Broadcast	
	Video Conferencing	Teamviewer Meeting	Teamviewer Meeting	
	Device management	DMS Cloud/Local	DMS Cloud/Local	




→ Specifications subject to change without notice. Please contact your local BenQ office for the full BenQ product range.


BenQ

INPUT AND OUTPUT TERMINALS


SIDE I/O




BOTTOM I/O




DIMENSIONS



IL4301



*IL5501



www.benq.eu/en-eu/business/index.html



© 2022 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

BenQ