

All Specifications

Display

Brightness (ANSI lumens)	2500
Native Resolution	1080P (1920x1080)
Native Aspect Ratio	16:9
Contrast Ratio (FOFO)	20,000:1
Display Color	30-bit (1.07 billion colors)
Light Source	4LED
Light Source Life	a. Normal 20000 hrs, b. ECO 30000 hrs

Optical

Throw Ratio	0.69-0.83
Zoom Ratio	1.2x
Projection Offset (Full-Height)	100%
Keystone Adjustment	2D, (Auto) Vertical ± 30 degrees; Horizontal ± 30 degrees

Picture

Rec. 709 Coverage	95%
Picture Modes	Bright, Golf, Presentation, sRGB, User 1, User 2, Video

Compatibility

Input Lag	33.4 ms (1080P 60Hz)
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB=Reduced blanking
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120Hz

I/O Interface

HDMI in	HDMI-1 (1.4a/HDCP1.4), HDMI-2 (1.4a/HDCP1.4)
USB Type A	USB Type A-1 (2.0/Power Supply1.5A)

Audio

Speaker	(x1), 10W
---------	-----------

Environment

Operating Temperature	0~40℃
Power Supply	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption (110V)	215W
Stand-by Power Consumption	<0.5W
Acoustic Noise (Typ./Eco.)(dB)	34dBA/28dBA

Accessories

Wireless USB dongle	(Optional)
Remote Control w/ Battery	RCX016
Power Cord (by region)	(Standard), x1 (1.8M)
3D Glasses	DGD5
Quick Start Guide	(x1) 21L
Warranty Card (by region)	Yes
Lens cover	Yes
Universal Ceiling Mount	(Optional), CM00G3

Smart System

Wi-Fi Standard	802.11b/g/n (2.4G/5G)
----------------	-----------------------

Dimension & Weight

Dimensions (WxHxD) (mm)	303.5*107.4.*220.7
Net Weight (kg)	2.65
Net Weight (lb)	5.84

Projection System

Projection System	DLP
-------------------	-----