

DIGITAL PROJECTOR

MH741

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



Features


- Full 1080p (1920x1080) resolution
- 4,000 ANSI lumens
- 10,000:1 high contrast ratio
- Full HD 3D support
- HDMI x 2, MHL
- Optional Wireless Presentation by Qcast



Specifications

Projection System	DLP®
Native Resolution	1080p (1920x 1080)
Brightness	4,000AL
Contrast Ratio	10,000:1
Display Color	1.07 Billion Colors
Lens	F=2.59~2.87, f=16.88~21.88mm)
Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
Throw Ratio	1.15-1.5(Wide 78.5" ±3% @ 2m)
Image Size	60"-300"
Zoom Ratio	1.3x
Lamp Type	260W
Lamp (Normal/Eco/SmartEco Mode)	2500/3500/4500 hours
Keystone Adjustment	2D, Horizontal +/- 30 degrees, Vertical +/- 30 degrees
Projection Offset	Vertical 130% ±5%
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)
Horizontal Frequency	15~102KHz
Vertical Scan Rate	23~120Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM 3D Compatibility: Frame Sequential: Up to 60Hz 720p Frame Packing: Up to 24 Hz 1080p Side by Side: Up to 24Hz 1080p Top Bottom: Up to 60Hz 1080p
Interface	Computer in (D-sub 15pin) x1 (integrate with component) HDMI x 2 (HDMI with MHL2.0 x1, HDMI x 1) MHL x 1 (HDMI with MHL2.0) Monitor out x 1 Composite Video in (RCA) x 1 S-Video in x 1 Audio in (Mini Jack) x 1 Audio in (L/R) x 1 Audio out (Mini Jack) x 1 Microphone in (mini Jack) x 1 Speaker 10W x 1 USB (Type A) x 1 (1.5A power supply) RS232 (DB-9pin) x 1 IR Receiver x2 (Front+Rear)
Dimensions (WxHxD)	12.3" x 4.5" x 8.5" (314.2 x 116 x 216.3mm) (include feet) 12.3" x 4.0" x 8.5" (314.2 x 102 x 216.3mm) (exclude)
Weight	7.28 lbs (3.3 Kg)
Power Supply	AC100 to 240V, 3.5A, 50 to 60 Hz
Power Consumption	330W(Normal), 270W(Eco), Standby <0.5W
Power Management Function	Automatic power off after 20 minutes without a display source
Audible Noise	36/31 dBA (Normal/Economic mode)
Languages	(28 Languages)
Picture Mode	**Dynamic / Presentation / sRGB / Cinema / (3D) / User 1 / User 2
Accessories (Standard)	Lens Cover, Remote Control w/ Battery, Power Cord, User Manual CD, Quick Start Guide, Warranty Card, VGA Cable
Accessories (Optional)	Spare Lamp Kit P/N: 5J.JEA05.001 Ceiling Mount Kit P/N: 5J.JAM10.001 3D Glasses P/N: 5J.J9H25.001 Carry Bag P/N: 5J.JCM09.001 QP01 Qcast Dongle P/N: 5J.JCK28.A01
UPC / Part #	8400460-3312-5 / 9H.JEA77.24A
Limited Warranty	1 Years Parts/Labor; 1 Year or 2,000 hours of lamp life

Input and Output Terminals



- 1 HDMI
- 2 HDMI-I/MHL
- 3 Audio in (Mini Jack)
- 4 Monitor Out (D-sub 15pin)
- 5 Computer In -1 / 2 (D-sub 15pin)
- 6 USB (TypeA)
- 7 CompositeVideo in (RCA)
- 8 S-Video (Mini DIN 4-pin)
- 9 Audio in (L/R)
- 10 Mic
- 11 Audio out (Mini Jack)
- 12 RS232 (DB-9pin)
- 13 USB (Type mini-B)

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.



BenQ America Corp.
 www.BenQ.us

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

MH741 | 10515_BQus



Because it matters