Mini Magnetic Stirrer



With a square footprint of under 5 inches, the MiniMag[™] is the most compact stirrer in the Benchmark line. Despite its modest dimensions, the 3.4 inch square work surface accepts a wide variety of beakers, flasks, bottles and other laboratroy vessels for stirring volumes as large as 1.5 liters.

The stirring speed is continuously adjustable from 100 to 1500rpm. For temperature sensitive samples, the MiniMag is incubator and cold-room safe for use from +4°C to +45°C.



Technical Data:

Speed Range: Platform Dimensions: Operating Temp. Range: Max. Stir Bar:

Dimensions: (WxDxH):

Weight: Electrical:

100 to 1500 rpm. 3.4 x 3.4 in. / 8.5 x 8.5 cm. +4 to +45°C

30 mm. 4.7 x 4.7 x 1.2 in. 12 x 12 x 3 cm.

0.45 lbs. (0.2kg) 100 to 240VAC, 50-60Hz 2W

(5V DC power supply) 1 year

Ordering Information:

S1005* MiniMag™ Mini Magnetic Stirrer

*Includes US plug. For Eu Plug, please add (-E).



Benchmark Scientific Inc. PO Box 709 Edison, NJ 08818 Phone: 908-769-5555

Fax: 732-313-7007

Web: www.BenchmarkScientific.com Email: Info@BenchmarkScientific.com