

# HERMLE *Benchmark*

## Z496-K *Series*

Z496-K  
Z496-K-UC

Ultra High Capacity Centrifuges



- **Ultra High Capacity** (4 x 1000ml, 40 x 50ml, 96 x 15ml)
- Accepts 500ml or 750ml blood bags
- Two models,
  - Floor-standing with storage drawer
  - Under-bench (27.5" height for use under the bench)



Z496-K *Underbench model*

### Z496-K Series Summary

Speed up to 10,500 rpm  
 G-Force up to 16,022 x g  
 Swing Out Capacity:  
 4 x 1000ml  
 4 x 500/750ml blood bags  
 40 x 50ml  
 96 x 15ml  
 24 x microplates

Angle Rotor Capacity  
 10 x 50ml  
 6 x 250ml  
 4 x 500ml

### Z496-K Features

Microprocessor Control  
 Over-speed protection  
 Automatic rotor identification  
 Program Storage (99)  
 Pre-Cool function  
 Momentary spin button  
 Imbalance detection  
 Adjustable Accel/Decel  
 Audible end of run alarm

Available underbench model  
 Maintenance free induction drive  
 Motor driven safety lid-lock  
 Quiet operation, less than 65 DB  
 Splash proof display  
 Powerful refrigeration  
 Storage drawer (Floor standing only)

### Z496-K Specifications

Speed Range: 200 to 10,500 rpm  
 Max. RCF: 16,022 xg  
 Max Capacity: 4 x 1000 ml  
 Timer: up to 99 hr, 59 min.  
 Dimensions: Underbench  
 24 x 27 x 27.5 in.  
 62 x 69 x 70 cm.  
 Floor Standing  
 24 x 27 x 38.6 in.  
 62 x 69 x 98 cm.  
 Weight: 346 lbs (157 kg)  
 Floor Standing 419 lbs (190 kg)  
 Electrical: 230V, 50/60Hz  
 Power Draw: 2300 W  
 Temp Range: -20° to 40° C



The Z496-K centrifuges offer the highest tube/bottle capacity in our range.

Several rotors are available, including a popular 4 position swinging bucket rotor with a wide offering of accessories for the centrifugation of tubes, bottles, plates and blood bags. The high capacity rectangular buckets accept microplates directly or a variety of tube inserts for accommodating as many as 40 x 50ml conical or 96 x 15ml conical tubes per run.

Advanced microprocessor controls allow for instant rotor identification, which automatically converts the rotational speed to the relevant g-force (rcf), preventing the user from setting a speed above the capabilities of the installed rotor. In addition to retrieving up to 99 saved programs, the easy to use front panel can adjust accel/decel rates, time, and convert operation between rpm and rcf. The powerful refrigeration system, with a range of -20° to 40° C, also features a precool function that ensures the temperature of the chamber is optimized for any application.

A standard floor standing model is available (height: 38.6 in.) which includes a convenient lower drawer for the storage of frequently used rotors and accessories. In addition, a space saving “underbench” model (height: 27.5 in.) is available when under the counter storage is preferred. Both models are equipped with wheels for easy maneuverability around the laboratory. W

For all your high capacity, high volume needs, the Z496-K floor standing series is the perfect centrifuge.

#### Ordering Information:

Z496-K\* Z496-K Floor Standing Centrifuge (without rotor)  
 Z496-K-UC\* Z496-K Underbench Centrifuge (without rotor)  
 \*Only available in 230V

# Universal Swing Out Rotor:



Item: Z496-1000-AC	
4 x 1000ml Swing Out Rotor	
Max Speed: 4,200 rpm / 3,964 xg (w Rectangular buckets)	
Accel: 84 sec. / Decel: 53 sec.	
Z496-1000-AC	Rotor without buckets
Z496-1000	Rotor complete with 4 rectangular buckets
Z496-1000-RBUK	Rectangular/Microplate buckets, 2/pk.
Z496-500-BLD	Bucket for 500ml blood bags, 2/pk (4,600 rpm / 5,298 xg)
Z496-750-BLD	Bucket for 750ml blood bags, 2/pk (4,600 rpm / 5,274 xg)
Z496-1000-1L	Round bucket for 1000ml bottles, 2/pk (4,600 rpm / 5,203 xg)
Z496-1000-MPRA	Microplate removing aid

Inserts: (rectangular buckets)	Tube/Bottle	qty/ insert	qty./ rotor
Z496-1000-A750	750ml	1	4
Z496-1000-A500	500ml	1	4
Z496-1000-A500C	500ml conical	1	4
Z496-1000-A250	250ml	2	8
Z496-1000-A225	175/225ml conical	2	8
Z496-1000-A100	100ml	3	12
Z496-1000-A50	50ml conical	10	40
Z496-1000-A50R	50ml round	10	40
Z496-1000-A15	15ml conical	24	96
Z496-1000-A5F	5ml conical	24	96
Z496-1000-A57	5/7ml	31	124

\*All inserts come in packs of 2\*

**New optional accessory!!!**

**Z326-MPCA**  
3 x chamber slide and dish carrier



Chamber Slides    35mm Dishes    60mm Dishes

Fits all Hermle microplate carriers!!!

**Z496-1000-RBUK**



**Z496-1000-1L**



**Blood bag buckets**



500ml



750ml



**Z496-1000-MPRA**  
Microplate removing aid



**Additional Rotors:**



<b>Item: Z446-0450</b>
4 x 500ml Angle Rotor (24°)
Max Speed: 8,000 rpm / 10,367 x g
Accel: 59 sec. / Decel: 81 sec.

Inserts/Adapters
Z446-500-A15: 15ml conical
Z446-500-A50R: 50ml round
Z446-500-A50: 50ml conical
Z446-500-A250: 250ml bottle



<b>Item: Z366-06250</b>
6 x 250ml Angle Rotor (28°)
Max Speed: 8,000 rpm / 10,016 x g
Accel: 53 sec. / Decel: 82 sec.

Inserts/Adapters
Z366-06250-A15: 4 x 15ml conical
Z366-06250-A50R: 50ml round
Z366-06250-A50: 50ml conical



<b>Item: Z326-1050</b>
10 x 50ml Angle Rotor (38°)
Max Speed: 10,500 rpm / 16,022 x g
Accel: 56 sec. / Decel: 64 sec.

Inserts/Adapters
Z326-50-A30: 30ml round
Z326-50-A15R: 15ml (conical or round)
Z206-50-A15: 15ml conical
Z206-50-A57: 5-7ml (12-13mm)
Z206-50-A57C: Cushion for 5ml tube

[www.hermleUSA.com](http://www.hermleUSA.com)  
PH: 908-769-5555 EM: [info@benchmarkscientific.com](mailto:info@benchmarkscientific.com)

**Also Available from Benchmark:**



**Z207 M**  
High Speed Microcentrifuge

- EZ-Scroll™ touch pad
- High speed, up to 17,317 x g
- Compact, 11in. wide
- Multiple rotor options for 1.5/2.0ml tubes



18 x 1.5/2.0ml  
spin column



24 x 1.5/2.0ml  
hermetically sealed