

Large Wax Dispenser

Part Numbers: 1456XL (115 VAC 50/60 Hz)
and 1456XL-2 (230 VAC 50/60 Hz)

The Boekel Large Wax Dispenser is ideal for larger histology laboratories that require large volumes of paraffin wax when embedding tissue samples. The Large Wax Dispenser has a maximum capacity of 28 liters (7.4 gallons) of wax and is the largest in the industry. This device can be used as the primary source of paraffin wax or to supplement tissue processors and embedding centers. The unit has a heated and filtered spigot to make sure the wax flows freely during operation. The advanced digital control system is easy to use and has a timer based Hot Start system that ensures the wax is melted prior to operation. The unit has a stainless-steel lid and chamber to stay corrosion free for years of use. Boekel Scientific is known worldwide for manufacturing high quality equipment and all histology equipment is designed and manufactured in the U.S.A and supplied with a two-year warranty.



Part Numbers	1456XL (115 VAC 50/60 Hz) 1456XL-2 (230 VAC 50/60 Hz)
Capacity	28 Liters / 7.4 gallons
Temperature Range	Ambient+5°C to 65°C
Accuracy	+/- 1.0°C
Default Temperature	55°C / 131°F
Overtemp Safety Cut Off	88°C / 190°F
Display	LCD with text and numeric display - Shows set temperature and Actual Temperature
Lid	Removable, Stainless Steel
Clock / Timer	Built in Clock for Automatic Starting - Hot Start

Features

- Industries largest wax capacity for high throughput use
- Adaptive digital control system that melts wax quickly and maintains the ideal temperature
- Hot Start feature will automatically start the warming based on set time to eliminate waiting
- Bright easy to use digital display
- Stainless steel lid and wax chamber to resist corrosion
- Heated and filtered wax spigot to keep the wax flowing quickly
- Two-year Warranty
- UL, CE, CSA approved

Large Wax Dispenser

Tap/Spigot	Heated, non-drip with a filter for particulates
Tap Height	9" from base. Will work with containers up to 9.5" tall
Electrical	1456XL (115 VAC 50/60 Hz) UL and CSA Certified
	1456XL-2 (230 VAC 50/60 Hz) CE Approved*
Power	750W, 6.5 amps for the 115V, 750W, 3.3 amps for the 230V
Regulatory	UL/CSA/CE - RoHs certified
Unit Dimensions	Width 14in/35.5cm x Depth 25.5in/65cm x Height 18.75in/48cm
Chamber Dimensions	Width 11.5in/29.2cm x Depth 19.25in/49cm x Height 7.5in/19cm
Weight (lbs/kg)	42 lbs / 19kg

