

STATIC SOLUTIONS WITH SAVINGS

ESD SAFE TAPES

CELLULOSE



Colored Striped Tapes

- B1613BS** Blue 1" x 3" 72YDS
- B1633BS** Blue 3/4" x 3" 72YDS
- B1653BS** Blue 1/2" x 3" 72YDS
- B1613RS** Red 1" x 3" 72YDS
- B1633RS** Red 3/4" x 3" 72YDS
- B1653RS** Red 1/2" x 3" 72YDS
- B1613YS** Yellow 1" x 3" 72YDS
- B1633YS** Yellow 3/4" x 3" 72YDS
- B1653YS** Yellow 1/2" x 3" 72YDS
- B1613GS** Green 1" x 3" 72YDS
- B1633GS** Green 3/4" x 3" 72YDS
- B1653GS** Green 1/2" x 3" 72YDS



Colored Printed Tapes

- B1613BPS** Blue 1" x 3" 72YDS
- B1633BPS** Blue 3/4" x 3" 72YDS
- B1653BPS** Blue 1/2" x 3" 72YDS
- B1613RPS** Red 1" x 3" 72YDS
- B1633RPS** Red 3/4" x 3" 72YDS
- B1653RPS** Red 1/2" x 3" 72YDS
- B1613YPS** Yellow 1" x 3" 72YDS
- B1633YPS** Yellow 3/4" x 3" 72YDS
- B1653YPS** Yellow 1/2" x 3" 72YDS
- B1613GPS** Green 1" x 3" 72YDS
- B1633GPS** Green 3/4" x 3" 72YDS
- B1653GPS** Green 1/2" x 3" 72YDS



Clear Tapes

- B1651** 1/2" x 1" 36YDS
- B1653** 1/2" x 3" 72YDS
- B1631** 3/4" x 1" 36YDS
- B1633** 3/4" x 3" 72YDS
- B1611** 1" x 1" 36YDS
- B1613** 1" x 3" 72YDS
- B1623** 2" x 3" 72YDS



Printed Tapes

- B1653P** 1/2" x 3" 72YDS
- B1633P** 3/4" x 3" 72YDS
- B1613P** 1" x 3" 72YDS
- B1623P** 2" x 3" 72YDS
- B1651P** 1/2" x 1" 36YDS
- B1631P** 3/4" x 1" 36YDS

ESD safe cellulose tape is 2.4 mil thick with a charge decay of <.014 seconds. Botron's anti-static tape is perfect for sealing ESD bags. It can also be used for a wide range of workstation applications such as binding, edging and securing.

TAPES

PROTECTIVE



Polymide Hi-Temp Tapes

- BK1643** 1/4" x 3" 36YDS
- BK1653** 1/2" x 3" 36YDS
- BK1633** 3/4" x 3" 36YDS
- BK1613** 1" x 3" 36YDS
- BK1653D** DUB/SIDE 1/2" x 3" A/S 36YDS



Low Static Hi-Temp Tapes

- BKA1608** 1/8" x 3" A/S 36YDS
- BKA1638** 3/8" x 3" A/S 36YDS
- BKA1643** 1/4" x 3" A/S 36YDS
- BKA1653** 1/2" x 3" A/S 36YDS
- BKA1678** 7/8" x 3" A/S 36YDS
- BKA1633** 3/4" x 3" A/S 36YDS
- BKA1613** 1" x 3" A/S 36YDS
- BKA1623** 2" x 3" A/S 36YDS



Conductive Grid Tapes

- B1605** 1/2" x 3" 118'
- B1635** 3/4" x 3" 118'
- B1615** 1" x 3" 118'
- B1620** 2" x 3" 118'



Hi-Temp Masking Tapes

- BHT53** 1/2" x 3" 60YDS
- BHT34** 3/4" x 3" 60YDS
- BHT13** 1" x 3" 60YDS
- BHT23** 2" x 3" 60YDS
- BHT33** 3" x 3" 60YDS

TAPES

AISLE MARKING



Aisle Marking Tapes

- B1618M** 3" x 54' Aisle Tape
- B1636M** 3" x 108' Aisle Tape



Lead Free Aisle Marking Tapes

- B1618L** 3" x 54' Two Color Aisle Tape

Hi-Temp polyimide tape will withstand temperatures up to 500F / 260C. Designed to minimize the effects of static generation during stripping and peeling. It is also highly resistant to heat and chemicals, puncture and tear resistant at high temperatures and offers optimal performance in electrical and thermal insulation.

Botron's anti-static grid tape most common usages are for electromagnetic interference (EMI) shielding and covering pins, connectors and plugs on electronic equipment during storage or transportation.

Hi-Temp masking tape withstands 275°f for 45 minutes. Designed for wave solder applications. It's rubber adhesive leaves virtually no residue and is stain free.

Botron's high visibility aisle marking tapes are perfect for marking off ESD safe areas and lead free zones.

