AUDIO SOLUTION

SoundLite 30W

SPEAKER SPECIFICATIONS		
Model	SoundLite 30W audio speaker and wireless microphone	
Amplifier	Class D amplifier	
Wattage Output	30W stereo	
Speaker Spec	2.75 in 15W/8 Ω x2 (high performance speaker)	
•		
SPL	92db/W	
Frequency Response	50Hz ~ 7kHz	
Dimensions	10 in x 9.8 in x 3.2 in / 25.4 cm x 24.89 cm x 8.13 cm	
Weight	3.3 lbs / 1.5 kg	
Color	White with black mesh	
Power Supply	Switching power supply DC19V / 2A (AC jack: 2 pin)	
Audio In	3.5mm	
Safety Certifications	CE, FCC, BSMI, NCC, CCC, SRRC	
Audio Auto Off	60 sec	
WIRELESS SPECIFICATIONS	RECEIVER (BUILT IN SPEAKER) TRANSM	ITTER (WIRELESS MODULE)
Voltage Range		3.6 ~ 5V
Current		<50mA
Frequency Response		2.4G ~ 2.483G
Channel	20 (channels (auto match)
Frequency Match		GFSK
Sensitivity	-85dBm (min)	
Output Resistance	32 Ω	
Output Voltage	2Vp-p (max)	
Transmitter Power		10mW
Input Resistance		10k Ω
Input Voltage		2.8Vp-p (max)
Power System		DX 5V (USB charge)
Audio In		Mic in/3.5MM audio in
AUX In		7 scales volume control
Audio Shift	<1.5ms	
Dynamix Range @1KHz	81db	
Separating Defree @1KHz		
Distortion THD	0.10%	
Match Time	3 sec	
Match Distance	6.6 ft <	(2 m<)
Operating Distance	98.4 ft	(30 m free space)
Battery Type	Lithium battery	
Battery Time	at least 8 hrs of use	
Battery Charge Time	4 hrs from dead battery to full charge	
Standby Power	under 0.5W	
MICROPHONE		
Microphone Type	Collar microphone and alternate hand held via transmitter	
Sensitivity	-37 db (f=1 KHz, S.P.L + 1Pa, OdB=1V/Pa)	
Signal to Noise Ratio	70db	
Maximum Input SPL	120db (F=1KHz, THD<1%)	
*Each Sound ite 30W peeds to be 5 m away from each other and within 3 m away to pair with the mic		

*Each SoundLite 30W needs to be 5 m away from each other and within 3 m away to pair with the mic

Award Winning Technical Support 24/7/365

BOXLIGHT

Presenting a Better Way

BOXLIGHT products come with free lifetime technical support. Speak with a hands-on, in-house, ISF Certified® technician ready to service your projector should the need arise.



KEY FEATURES

• Latest digital speaker system, combines high efficiency speaker and wireless microphone into one 30W dual channel Class D amplifier system with high efficiency and full range speakers

• AUX in and Mic in audio source with four output modes (single, karaoke, mic priority and voice command)

• Two hook assembly design for fast installation

• Microphone priority allows for audio pause during presentations to enable speaking priority

The transmitter can be used as a stand-alone mic as well as match to multiple inputs including other audio players, music players and cell phones
Portable



Advantages of 2.4GHz technology

• The SoundLite 30W uses frequency expansion technology to reduce the signal noise and enhance the transmission reliability

• 2.4G has low power consumption for long operation time, and the frequency auto-matching and multi-transmission function make it easy to use







Fax: (732)-222-7088 | E-mail: sales@touchboards.com

360.464.2119 www.BOXLIGHT.com

© 2014 BOXLIGHT, Inc. Specifications subject to change without notice. Helps meet ADA Section 508 compliance BOXLIGHT | NE 151 Highway 300, Suite A | PO Box 2609 | Belfair, WA 98528