

Specifications

Key Characteristics	Catalog Page #	300
	Product Number	121123
	UPC	754473706210
	Applications	Arrow Tape, Floor Marking, Pipe & Valve Marking, Safety & Compliance ID, Warehouse Marking
	UOM	Roll of 50 Feet
	Brand Name	Brady®
	Country of Origin	United States of America
	HTS Code (Harmonized Tariff Schedule)	3919.10.2055
	ECCN (Export Commodity Control Number)	EAR99
Dimensions	Dimensions	0.25 in W x 50 ft L
	Width	0.25 in
	Length	50 ft
	Roll/Tape Length	50 ft
	Roll Width	0.25 in
	Thickness	0.004 in
Material Characteristics	Material Number	B-7569 (View Technical Data Sheet)
	Material	Vinyl
	Adhesive Type	Permanent Acrylic
	Finish	Gloss
	Color	Blue
	Resistance Properties	Abrasion-Resistant, Chemical-Resistant
	Indoor or Outdoor Use	Outdoor Use
	Service Temperature Range °F	-4 °F - 167 °F
	Minimum Service Temperature °F	-4 °F
	Minimum Service Temperature °F	-4 °F
	Maximum Service Temperature °F	167 °F
	Minimum Application Temperature °F	50 °F
	Reflective Type	Non-Reflective
	PSPA Photoluminescence Class	Not Rated
	Compatible Surface Types	Curved, General
Product Features	Application	Lockout Tagout, Safety Identification, Warehouse Marking
	Average Outdoor Durability	3 Years
Preprinted Information	Text Legend	No Text Legend
Compliance	UNSPSC	41122703
	RoHS Compliance Status	Not applicable to this product

Specifications

Key Characteristics	<u>Catalog Page #</u>	300
	Product Number	121129
	UPC	754473706357
	<u>Applications</u>	Arrow Tape, Floor Marking, Pipe & Valve Marking, Safety & Compliance ID, Warehouse Marking
	UOM	Roll of 50 Feet
	Brand Name	Brady®
	<u>Country of Origin</u>	United States of America
	<u>HTS Code (Harmonized Tariff Schedule)</u>	3919.10.2055
	<u>ECCN (Export Commodity Control Number)</u>	EAR99
Dimensions	Dimensions	0.5 in W x 50 ft L
	Width	0.5 in
	Length	50 ft
	Roll/Tape Length	50 ft
	Roll Width	0.5 in
	Thickness	0.004 in
Material Characteristics	<u>Material Number</u>	B-7569 (View Technical Data Sheet)
	<u>Material</u>	Vinyl
	Adhesive Type	Permanent Acrylic
	Finish	Gloss
	Color	Yellow
	Resistance Properties	Abrasion-Resistant, Chemical-Resistant
	Indoor or Outdoor Use	Outdoor Use
	Service Temperature Range °F	-4 °F - 167 °F
	Minimum Service Temperature °F	-4 °F
	Minimum Service Temperature °F	-4 °F
	Maximum Service Temperature °F	167 °F
	Minimum Application Temperature °F	50 °F
	<u>Reflective Type</u>	Non-Reflective
	<u>PSPA Photoluminescence Class</u>	Not Rated
	Compatible Surface Types	Curved, General
Product Features	<u>Application</u>	Lockout Tagout, Safety Identification, Warehouse Marking
	<u>Average Outdoor Durability</u>	3 Years
Preprinted Information	Text Legend	No Text Legend
Compliance	<u>UNSPSC</u>	41122703
	RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863

Specifications

Key Characteristics	Catalog Page #	300
	Product Number	121130
	UPC	754473706364
	<u>Applications</u>	Arrow Tape, Floor Marking, Pipe & Valve Marking, Safety & Compliance ID, Warehouse Marking
	UOM	Roll of 50 Feet
	Brand Name	Brady®
	<u>Country of Origin</u>	United States of America
	<u>HTS Code (Harmonized Tariff Schedule)</u>	3919.10.2055
	<u>ECCN (Export Commodity Control Number)</u>	EAR99
Dimensions	Dimensions	0.5 in W x 50 ft L
	Width	0.5 in
	Length	50 ft
	Roll/Tape Length	50 ft
	Roll Width	0.5 in
	Thickness	0.004 in
Material Characteristics	<u>Material Number</u>	B-7569 (View Technical Data Sheet)
	<u>Material</u>	Vinyl
	Adhesive Type	Permanent Acrylic
	Finish	Gloss
	Color	Green
	Resistance Properties	Abrasion-Resistant, Chemical-Resistant
	Indoor or Outdoor Use	Outdoor Use
	Service Temperature Range °F	-4 °F - 167 °F
	Minimum Service Temperature °F	-4 °F
	Minimum Service Temperature °F	-4 °F
	Maximum Service Temperature °F	167 °F
	Minimum Application Temperature °F	50 °F
	<u>Reflective Type</u>	Non-Reflective
	<u>PSPA Photoluminescence Class</u>	Not Rated
	Compatible Surface Types	Curved, General
Product Features	<u>Application</u>	Lockout Tagout, Safety Identification, Warehouse Marking
	<u>Average Outdoor Durability</u>	3 Years
Preprinted Information	Text Legend	No Text Legend
Compliance	<u>UNSPSC</u>	41122703
	RoHS Compliance Status	Not applicable to this product

Specifications

Key Characteristics	<u>Catalog Page #</u>	300
	Product Number	121128
	UPC	754473706340
	<u>Applications</u>	Arrow Tape, Floor Marking, Pipe & Valve Marking, Safety & Compliance ID, Warehouse Marking
	UOM	Roll of 50 Feet
	Brand Name	Brady®
	<u>Country of Origin</u>	United States of America
	<u>HTS Code (Harmonized Tariff Schedule)</u>	3919.10.2055
	<u>ECCN (Export Commodity Control Number)</u>	EAR99
Dimensions	Dimensions	0.5 in W x 50 ft L
	Width	0.5 in
	Length	50 ft
	Roll/Tape Length	50 ft
	Roll Width	0.5 in
	Thickness	0.004 in
Material Characteristics	<u>Material Number</u>	B-7569 (View Technical Data Sheet)
	<u>Material</u>	Vinyl
	Adhesive Type	Permanent Acrylic
	Finish	Gloss
	Color	Blue
	Resistance Properties	Abrasion-Resistant, Chemical-Resistant
	Indoor or Outdoor Use	Outdoor Use
	Service Temperature Range °F	-4 °F - 167 °F
	Minimum Service Temperature °F	-4 °F
	Minimum Service Temperature °F	-4 °F
	Maximum Service Temperature °F	167 °F
	Minimum Application Temperature °F	50 °F
	<u>Reflective Type</u>	Non-Reflective
	<u>PSPA Photoluminescence Class</u>	Not Rated
	Compatible Surface Types	Curved, General
Product Features	<u>Application</u>	Lockout Tagout, Safety Identification, Warehouse Marking
	<u>Average Outdoor Durability</u>	3 Years
Preprinted Information	Text Legend	No Text Legend
Compliance	<u>UNSPSC</u>	41122703
	RoHS Compliance Status	Not applicable to this product