

| | | |
|---------------------|--|--------------------------|
| Key Characteristics | Catalog Page # i | 472 |
| | Product Number | 84853 |
| | UPC | 754473848538 |
| | UOM | Sign |
| | Brand Name | Brady® |
| | Country of Origin i | United States of America |
| | HTS Code (Harmonized Tariff Schedule) i | 4911.99.8000 |
| | ECCN (Export Commodity Control Number) i | EAR99 |

| | | |
|------------|-------------------|------------------|
| Dimensions | Sign Size (H x W) | 7" x 10" |
| | Dimensions | 7 in H x 10 in W |
| | Height | 7 in |
| | Width | 10 in |
| | Depth | 0.006 in |
| | Thickness | 0.006 in |

| | | |
|--------------------------|--|---|
| Material Characteristics | Material Number i | B-302 (View Technical Data Sheet) |
| | Material i | Polyester with Polyester Overlamine |
| | Adhesive Type | Permanent Acrylic |
| | Color | Black on Yellow |
| | Resistance Properties | Abrasion-Resistant, Chemical-Resistant |
| | Laminated | Laminated |
| | Indoor or Outdoor Use | Outdoor Use |
| | Service Temperature Range °F | -40 °F - 230 °F |
| | Minimum Service Temperature °F | -40 °F |
| | Minimum Service Temperature °F | -40 °F |
| | Maximum Service Temperature °F | 230 °F |
| | Minimum Application Temperature °F | 0 °F |
| | Reflective Type i | Non-Reflective |
| | Illumination | Not Illuminated |
| | PSPA Photoluminescence Class i | Not Illuminated |
| | Compatible Surface Types | Cold, High Surface Energy |