






# Specifications



## Key Characteristics

Catalog Page # 	40
Product Number	142034
UPC	754473183417
Applications 	Arc Flash Labels, Arrow Tape, Pipe & Valve Marking, Safety & Compliance ID, Visual Workplace Labeling, Warehouse Marking
UOM	Cartridge of 100 Feet
Trade Name	B30
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

## Dimensions



Label/Tape Size	2.25 in W x 100 ft L
Roll Length	100 ft
Roll Width	2.25 in
Thickness	0.004 in
Web Width	2.5 in

## Material Characteristics

Material Number 	<a href="#">B-595 (View Technical Data Sheet)</a>
Material 	Vinyl
Label Properties	Aggressive Adhesive, Harsh Environment, Outdoor Durable, Permanent Adhesive
Adhesive Type	Permanent Acrylic
Finish	Gloss
Color	Yellow
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Oil-Resistant, Water-Resistant
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-40 °F - 180 °F
Minimum Service Temperature °F	-40 °F
Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	180 °F

Minimum Application Temperature °F	0 °F
Compatible Surface Types	General


#### Product Features

Application 	Component and Equipment Labeling, Electrical Labeling, Facility Identification, Floor Marking, Laboratory Labeling, Lean and 5S Labeling, Pipe and Valve Marking, Warehouse Marking
Average Outdoor Durability 	8 to 10 Years
Label/Media Format	Roll
Quantity per Row	1

#### Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

#### Compatibility

Printer Compatibility	BBP30, BBP31, BBP33, BBP35, BBP37, i3300, i5300, S3000, S3100
Recommended Ribbon 	B30-R10000
Suggested Ribbon Series	R10000

#### Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863