






Specifications



Key Characteristics

Catalog Page # 	40
Product Number	142019
UPC	754473183264
Applications 	Arc Flash Labels, Arrow Tape, Pipe & Valve Marking, Safety & Compliance ID, Visual Workplace Labeling, Warehouse Marking
UOM	Cartridge of 100 Feet
Trade Name	B30
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions



Label/Tape Size	4 in W x 100 ft L
Roll Length	100 ft
Roll Width	4 in
Thickness	0.004 in
Web Width	4.25 in

Material Characteristics

Material Number 	B-595 (View Technical Data Sheet)
Material 	Vinyl
Label Properties	Aggressive Adhesive, Harsh Environment, Outdoor Durable, Permanent Adhesive
Adhesive Type	Permanent Acrylic
Finish	Gloss
Color	Purple
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Oil-Resistant, Water-Resistant
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-40 °F - 180 °F
Minimum Service Temperature °F	-40 °F
Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	180 °F

Minimum Application Temperature °F	0 °F
Compatible Surface Types	General


Product Features

Application 	Component and Equipment Labeling, Electrical Labeling, Facility Identification, Floor Marking, Laboratory Labeling, Lean and 5S Labeling, Pipe and Valve Marking, Warehouse Marking
Average Outdoor Durability 	8 to 10 Years
Label/Media Format	Roll
Quantity per Row	1

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP30, BBP31, BBP33, BBP35, BBP37, i3300, i5300, S3000, S3100
Recommended Ribbon 	B30-R10000-WT
Suggested Ribbon Series	R10000

Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863