

Catalog Page # 	119
Product Number	143227
UPC	754473082918
Applications 	Cable & Wire Marking, Panel Labeling
UOM	Cartridge of 80 Each
Quantity per Roll	80
Unit Price	\$0.71/Sleeve
Quantity per Row	1
Trade Name	PermaSleeve®
Brand Name	Brady®
Ribbon Series	R4300
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.335 in H x 1 in W
Height	0.335 in
Width	1 in
Roll Width	1 in
Sleeve Size	0.187 in Dia x 1 in W
Sleeve Width	1 in
Recovered Diameter	0.062 in
Web Width	1.812 in
Diameter as Supplied	0.187 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	Black on White
Ribbon Color	Black
Tape Color	White
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant
Shrink Ratio 	3:1

Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	275 °F

Product Features

Application 	Electrical Labeling, Wire and Cable Labeling
Label/Media Format	Label/Media in Cartridge with Ribbon
Printable Sides	Single-Side Printable

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BMP51, BMP53
Wire Diameter Range	0.062 in to 0.15 in
Wire Gauge Range 	20 AWG - 10 AWG

Compliance

UNSPSC 	39131502
California Prop 65 	 WARNING: Cancer - www.p65warnings.ca.gov
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863