

Specifications

Key Characteristics

Catalog Page # 	156
Product Number	114797
UPC	662820925842
Applications 	Asset Tracking, Barcode Labeling, Circuit Board ID - Through Hole Top, Component & Equipment ID, General & Industrial ID, Rating Plates
UOM	Roll of 500 Labels
Quantity per Roll	500
Unit Price	\$0.00/Label
Trade Name	WorkHorse®
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550

Dimensions

Dimensions	0.5 in H x 1.5 in W
Height	0.5 in
Width	1.5 in
Label/Tape Size	0.5 in H x 1.5 in W
Printable Area Dimensions 	0.5 in H x 1.5 in W
Printable Area Height	0.5 in
Printable Area Width	1.5 in

Thickness	0.0031 in
Vertical Repeat	0.625 in

Material Characteristics

Material Number 	B-459 (View Technical Data Sheet)
Material 	Polyester
Label Properties	Harsh Environment, Permanent Adhesive
Adhesive Type	Permanent Acrylic
Finish	Matte
Color	White
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, UV-Resistant, Weather-Resistant
Service Temperature Range °F	-40 °F - 212 °F
Minimum Service Temperature °F	-40 °F
Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	212 °F
Compatible Surface Types	High Surface Energy

Product Features

Application 	Circuit Board Labeling
Shape	Rectangle
Label/Media Format	Roll
Quantity per Row	1

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BMP71
Recommended Ribbon 	M71-R6000
Suggested Ribbon Series	R4400, R6000 Halogen Free, R6900

Preprinted Information

Pre-Printed Areas on Label	Colored Write-On Area
----------------------------	-----------------------

What's Included

Secondary Label Included	Secondary Label is Not Included
--------------------------	---------------------------------

Compliance

UNSPSC 	55121612
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information