








Catalog Page # 	165
Product Number	114981
UPC	662820927327
Applications 	Cable & Wire Marking, Panel Labeling
UOM	Roll of 100 Each
Quantity per Roll	100
Unit Price	\$1.52/Sleeve
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550

Dimensions

Dimensions	0.645 in H x 1.75 in W
Height	0.645 in
Width	1.75 in
Roll Width	1.75 in
Sleeve Size	0.375 in Dia x 1.75 in W
Sleeve Width	1.75 in
Vertical Repeat	1 in
Recovered Diameter	0.125 in
Recovered Wall Thickness	0.025 in
Web Width	2.25 in
Diameter as Supplied	0.375 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	Yellow
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant
Shrink Ratio 	3:1
Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	275 °F

Product Features



Application 	Electrical Labeling, Wire and Cable Labeling
Label/Media Format	Roll
Printable Sides	Single-Side Printable
Quantity per Row	1
Sleeve Slits	No

Printing Specifications



Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BMP71
-----------------------	-------

Recommended Ribbon 	M71-R4300
Suggested Ribbon Series	R4300, R4502S, R5000, R6600, R6700
Wire Diameter Range	0.125 in to 0.32 in
Wire Gauge Range 	12 AWG - 4 AWG

Compliance

UNSPSC 	39131502
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information