

Specifications

Key Characteristics

Catalog Page # 	199
Product Number	32137
UPC	662820321378
Applications 	Cable & Wire Marking
UOM	Roll of 500 Each
Quantity per Roll	500
Unit Price	\$0.55/Sleeve
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.235 in H x 1.5 in W
Height	0.235 in
Width	1.5 in
Roll Width	1.5 in
Sleeve Size	0.125 in Dia x 1.5 in W
Sleeve Width	1.5 in
Vertical Repeat	0.5 in
Recovered Diameter	0.046 in
Recovered Wall Thickness	0.02 in
Web Width	3.49 in
Diameter as Supplied	0.125 in
Core Diameter	3 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink

Finish	Matte
Color	White
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant
Shrink Ratio 	3:1
Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	275 °F

Product Features

Application 	Wire and Cable Labeling
Label/Media Format	Roll
Printable Sides	Single-Side Printable
Quantity per Row	1
Sleeve Slits	No

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP11, BBP12, BBP72, i5100, i7100, IP Series, PR Plus, THT 3" Core Printers
Recommended Ribbon 	IP-R6606, R6606
Suggested Ribbon Series	R4300, R4502S, R5000, R6600, R6700
Wire Diameter Range	0.046 in to 0.11 in
Wire Gauge Range 	22 AWG - 16 AWG

Compliance

UNSPSC 	39131502
California Prop 65 	 WARNING: Cancer - www.p65warnings.ca.gov
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863