









Catalog Page # 	138
Product Number	114360
UPC	662820922551
Applications 	Cable & Wire Marking
UOM	Roll of 100 Each
Quantity per Roll	100
Unit Price	\$1.78/Sleeve
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99



## Dimensions

Dimensions	0.182 in H x 1 in W
Height	0.182 in
Width	1 in
Roll Width	1 in
Sleeve Size	0.094 in Dia x 1 in W
Sleeve Width	1 in
Vertical Repeat	0.5 in
Recovered Diameter	0.031 in
Web Width	1.812 in
Diameter as Supplied	0.094 in

## Material Characteristics

Material Number 	B-345 ( <a href="#">View Technical Data Sheet</a> )
Material 	High Temperature Heat-shrink Polyvinylidene Fluoride Sleeve
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	Yellow
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, High Temperature-resistant, Humidity-Resistant, UV-Resistant, Weather-Resistant
Shrink Ratio 	2:1 (3:1 for 0.094" Dia)
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-67 °F - 437 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	437 °F



## Product Features

Application 	Wire and Cable Labeling
Average Outdoor Durability 	2 Years
Label/Media Format	Roll
Printable Sides	Single-Side Printable
Quantity per Row	1
Sleeve Slits	No



## Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

## Compatibility

Printer Compatibility	BMP61, BMP71 (with media adapter)
Recommended Ribbon 	M61-R6010, M71-R6000
Suggested Ribbon Series	R4400W, R6000 Halogen Free, R6600, R6800
Wire Diameter Range	0.031 in to 0.08 in
Wire Gauge Range 	26 AWG - 20 AWG

## Compliance

UNSPSC 	39131502
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information