

Specifications

Key Characteristics

Catalog Page # 	145
Product Number	18376
UPC	662820183761
Applications 	General & Industrial ID, Panel Labeling
UOM	Roll of 100 Labels
Quantity per Roll	100
Unit Price	\$0.00/Label
Trade Name	BMP®61 BMP®71 TLS 2200® TLS-PC Link™
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	1 in H x 2 in W
Height	1 in
Width	2 in
Label/Tape Size	1 in H x 2 in W
Printable Area Dimensions	2 in H x 1 in W
Printable Area Height	2 in

Printable Area Width	1 in
Thickness	0.0035 in
Vertical Repeat	2.125 in
Web Width	1.312 in
Core Diameter	1 in

Material Characteristics

Material Number 	B-424 (View Technical Data Sheet)
Material 	Paper
Label Properties	Permanent Adhesive
Adhesive Type	Permanent Rubber Based
Finish	Matte
Color	White
Resistance Properties	Abrasion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant
Indoor or Outdoor Use	Indoor Use
Service Temperature Range °F	-40 °F - 122 °F
Minimum Service Temperature °F	-40 °F
Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	122 °F
Compatible Surface Types	Low Surface Energy

Product Features

Application 	Barcode Labeling, Electrical Labeling, General Identification, Laboratory Labeling
---	--

Shape	Rectangle
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	1

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BMP61, BMP71 (with media adapter)
Recommended Ribbon 	M61-R4310, M71-R4300
Suggested Ribbon Series	R4300

Preprinted Information

Pre-Printed Areas on Label	Colored Write-On Area
----------------------------	-----------------------

Compliance

UNSPSC 	55121612
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information