









Catalog Page # 	132
Product Number	18515
UPC	662820185154
Applications 	Cable & Wire Marking, Laboratory ID - Bottle, Tube & Vial, Panel Labeling, Voice & Data ID
UOM	Roll of 100 Labels
Quantity per Roll	100
Unit Price	\$0.00/Label
Trade Name	BMP®61 BMP®71 TLS 2200® TLS-PC Link™
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

## Dimensions


Dimensions	2.5 in H x 1 in W
Height	2.5 in
Width	1 in
Label/Tape Size	2.5 in H x 1 in W
Printable Area Dimensions 	0.75 in H x 1 in W
Printable Area Height	0.75 in
Printable Area Width	1 in
Thickness	0.004 in
Vertical Repeat	2.625 in
Web Width	1.312 in

Vial/Tube Size	0.5 ml
Core Diameter	1 in

## Material Characteristics

Material Number 	<a href="#">B-427 (View Technical Data Sheet)</a>
Material 	Self-laminating Vinyl
Material Properties	Flame-retardant, Self-laminating
Label Properties	Self Laminating & Wrap Around
Adhesive Type	Permanent Acrylic
Finish	Matte
Color	Purple, Clear
Resistance Properties	Chemical-Resistant, Humidity-Resistant, Oil-Resistant, Water-Resistant, Weather-Resistant
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-94 °F - 158 °F
Minimum Service Temperature °F	-94 °F
Minimum Service Temperature °F	-94 °F
Maximum Service Temperature °F	158 °F
Compatible Surface Types	General



## Product Features

Application 	Data and Telecommunications Labeling, Electrical Labeling, Laboratory Labeling, Wire and Cable Labeling
Shape	Rectangle
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	1

## Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

## Compatibility

Printer Compatibility	BMP61, BMP71 (with media adapter)
Recommended Ribbon 	M61-R4310, M71-R4300
Suggested Ribbon Series	R4300, R4500
Wire Diameter Range	0.264 in to 0.559 in
Wire Gauge Range 	6 AWG - 000 AWG



## Preprinted Information

Pre-Printed Areas on Label	Colored Write-On Area
----------------------------	-----------------------

## What's Included

Overlamine Included	Overlamine Included
Secondary Label Included	Secondary Label is Not Included

## Compliance

UNSPSC 	55121612
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information