

Specifications

Key Characteristics

Catalog Page # 	178
Product Number	146028
UPC	754473548872
Applications 	Circuit Board ID - After Process, Circuit Board ID - Surface Mount, Circuit Board ID - Through Hole Bottom, Circuit Board ID - Through Hole Top, Component & Equipment ID
UOM	Roll of 10000 Labels
Quantity per Roll	10000
Unit Price	\$0.06/Label
Trade Name	UltraTemp®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.2 in H x 0.65 in W
Height	0.2 in
Width	0.65 in
Label/Tape Size	0.2 in H x 0.65 in W
Thickness	0.0044 in
Horizontal Repeat	0.7 in
Vertical Repeat	0.3 in
Web Width	2.95 in
Core Diameter	3 in

Material Characteristics

Material Number 	B-776 (View Technical Data Sheet)
Material 	Polyimide
Label Properties	Heat Resistant, Permanent Adhesive
Adhesive Type	Permanent Acrylic
Finish	Gloss
Color	Light Green

Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Temperature-Resistant
Indoor or Outdoor Use	Indoor Use
Service Temperature Range °F	-94 °F - 572 °F
Minimum Service Temperature °F	-94 °F
Minimum Service Temperature °F	-94 °F
Maximum Service Temperature °F	572 °F
Compatible Surface Types	High Surface Energy

Product Features

Application 	Circuit Board Labeling, Component and Equipment Labeling
Shape	Rectangle
Average Outdoor Durability 	Not Recommended
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	4

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP81, i5100, i7100, IP Series, PR Plus, THT 3" Core Printers
Recommended Ribbon 	IP-R6002, R6002
Suggested Ribbon Series	R6000 Halogen Free

Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863