






Specifications



Key Characteristics

Catalog Page # 	159
Product Number	11263
UPC	662820112631
Applications 	Laboratory ID - Bottle, Tube & Vial, Laboratory ID - Centrifuge Tube, Laboratory ID - Eppendorf Tube
UOM	Roll of 3000 Labels
Quantity per Roll	3000
Unit Price	\$0.06/Label
Trade Name	FreezerBondz™
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions


Dimensions	0.375 in H x 1.25 in W
Height	0.375 in
Width	1.25 in
Label/Tape Size	0.375 in H x 1.25 in W
Printable Area Dimensions 	0.375 in H x 1.25 in W
Printable Area Height	0.375 in
Printable Area Width	1.25 in
Thickness	0.0026 in
Vertical Repeat	0.5 in
Web Width	1.45 in
Vial/Tube Size	0.5 - 0.7 ml
Core Diameter	3 in

Material Characteristics

Material Number 	B-490 (View Technical Data Sheet)
Material 	FreezerBondz™ Polyester
Material Properties	Autoclavable, Cold-temperature application, Cryogenic storage
Label Properties	Aggressive Adhesive, Low Temperature

Adhesive Type	Permanent Acrylic
Finish	Matte
Color	White
Resistance Properties	Chemical-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant
Indoor or Outdoor Use	Indoor Use
Service Temperature Range °F	-320 °F - 266 °F
Minimum Service Temperature °F	-320 °F
Minimum Service Temperature °F	-320 °F
Maximum Service Temperature °F	266 °F
Minimum Application Temperature °F	-320 °F
Compatible Surface Types	Cold, High Surface Energy


Product Features

Application 	Laboratory Labeling
Shape	Rectangle
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	1

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP81, i5100, i7100, IP Series, PR Plus, THT 3" Core Printers
Recommended Ribbon 	IP-R4306, R4306
Suggested Ribbon Series	R4300

Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863