




# Specifications

## Key Characteristics

Product Number	150508
UPC	754473615437
UOM	Kit
Brand Name	Code Corporation
Country of Origin 	Malaysia
HTS Code (Harmonized Tariff Schedule) 	8471.60.8000
ECCN (Export Commodity Control Number) 	EAR99

## Dimensions








Dimensions	5.2 in H x 2 in W x 3 in D
Height	5.2 in
Width	2 in
Depth	3 in
Cable Length	6 ft
Weight	0.26 lb

## Material Characteristics

Color	Dark Gray
-------	-----------

## Product Features

Connectivity Options 	USB
--	-----

Scanner Model	CR1500
Battery Type	No Battery
Decode Capability - 1D	BC412, Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, GS1 DataBar, Hong Kong 2 of 5, IATA 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI Plessey, NEC 2 of 5, Pharmacode, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC / EAN / JAN
Rotational Tolerance	+/- 180°
Sensor 	CMOS 1.2 Megapixel
Field of View 	High Density Field: 30° Horizontal by 20° Vertical, Wide Field: 50° Horizontal by 33.5° Vertical
Focal Point 	Approximately 100 mm
Optical Resolution 	High Density Field: 960 x 640, Wide Field: 960 x 640
Pitch 	± 65° (from front to back)
Skew 	± 60° from plane parallel to symbol (side-to-side)
Target Beam 	Single Blue targeting bar (470nm)
Image Output Options	JPEG, PGM
Decode Capability - 1D Stacked	Codablock F, Code 49, GS1 Composite (CC-A/CC-B/CC-C), MicroPDF, PDF417
Decode Capability - 2D	Aztec Code, Data Matrix, Data Matrix Rectangular Ext'n, GoCode® (proprietary--add'l license req'd), Grid Matrix, HanXin Code, Micro QR Code, QR Code, QR Model 1
Decode Capability - Postal	Australian Post, Canada Post, Intelligent Mail, Japan Post, KIX Code, Korea Post, Planet, Post-Net, UK Royal Mail, UPU ID-tags
Field Selection	High Density or Wide Field
Advanced Data Editing	JavaScript

Symbol Contrast	15% minimum reflectance difference
Ambient Light Immunity	Sunlight: Up to 9,000ft-candles/96,890 lux
Charging Station Communication Interfaces for Barcode Scanners	RS232, USB 2.0 (generic HID, HID keyboard, virtual com port)




## Printing Specifications

Device Drop Test & Durability	Resistant to 6-foot drops
-------------------------------	---------------------------

## What's Included

Includes	(1) CR1500 Reader, (1) Stand, (1) USB Cable 6ft
----------	---

## Compliance

UNSPSC 	43211701
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
Ingress Protection Rating 	IP54
RoHS Compliance Status	Please contact our CS department for more information