






## Specifications

### Key Characteristics

Catalog Page # 	48
Product Number	143017
UPC	662820968573
Applications 	Component & Equipment ID, Laboratory ID - Bottle, Tube & Vial, Laboratory ID - Centrifuge Tube, Laboratory ID - Eppendorf Tube, Panel Labeling
UOM	Cartridge of 1500 Labels
Quantity per Roll	1500
Unit Price	\$0.06/Label
Trade Name	BBP@33
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

### Dimensions



Dimensions	0.375 in H x 1 in W
Height	0.375 in
Width	1 in
Label/Tape Size	0.375 in H x 1 in W
Thickness	0.0065 in
Horizontal Repeat	1.1 in
Vertical Repeat	0.475 in
Web Width	2.3 in
Vial/Tube Size	0.5 - 0.7 ml

### Material Characteristics

Material Number 	<a href="#">B-499 (View Technical Data Sheet)</a>
Material 	Nylon Cloth
Material Properties	Autoclavable, Cryogenic storage, Halogen-free
Label Properties	Aggressive Adhesive, Low Temperature, Permanent Adhesive
Adhesive Type	Permanent Acrylic
Finish	Matte
Color	White

Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Humidity-Resistant, Low Temperature-Resistant, UV-Resistant, Weather-Resistant
Indoor or Outdoor Use	Indoor Use
Service Temperature Range °F	-40 °F - 194 °F
Minimum Service Temperature °F	-40 °F
Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	194 °F
Compatible Surface Types	High Surface Energy


#### Product Features

Application 	Component and Equipment Labeling, Electrical Labeling, General Identification, Laboratory Labeling, Warehouse Marking, Wire and Cable Labeling
Shape	Rectangle
Average Outdoor Durability 	Not Recommended
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	2

#### Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

#### Compatibility

Printer Compatibility	BBP33, i3300, i5300
Recommended Ribbon 	B30-R4300
Suggested Ribbon Series	R4300, R4500, R4900, R6000 Halogen Free, R6200

#### Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863