






Specifications



Key Characteristics

Catalog Page # 	54
Product Number	143085
UPC	662820969259
Applications 	Asset Tracking, General & Industrial ID
UOM	Cartridge of 1500 Labels
Quantity per Roll	1500
Unit Price	\$0.09/Label
Trade Name	MetaLabel
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions



Dimensions	1 in H x 2 in W
Height	1 in
Width	2 in
Label/Tape Size	1 in H x 2 in W
Thickness	0.0047 in
Vertical Repeat	1.125 in
Web Width	2.2 in

Material Characteristics

Material Number 	B-428 (View Technical Data Sheet)
Material 	Metallized Polyester
Material Properties	Metallic Appearance
Label Properties	Heat Resistant, Metallic, Permanent Adhesive
Adhesive Type	Permanent Acrylic
Finish	Matte
Color	Light Gray
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, UV-Resistant, Weather-Resistant
Indoor or Outdoor Use	Indoor Use

Service Temperature Range °F	-40 °F - 248 °F
Minimum Service Temperature °F	-40 °F
Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	248 °F
Compatible Surface Types	High Surface Energy


Product Features

Application 	Asset Tracking, Circuit Board Labeling, Component and Equipment Labeling, Data and Telecommunications Labeling, General Identification, Inventory and Inspection Labeling
Shape	Rectangle
Average Outdoor Durability 	2 Years
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	1

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP33, i3300, i5300
Recommended Ribbon 	B30-R4300
Suggested Ribbon Series	R4300, R4500, R6200

Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863