

Specifications

Key Characteristics	Catalog Page # 	56
	Product Number	140732
	UPC	754473939014
	Applications 	Circuit Board ID - After Process, Circuit Board ID - Surface Mount, Circuit Board ID - Through Hole Bottom, Circuit Board ID - Through Hole Top, Circuit Board Marking
	UOM	Cartridge of 2500 Labels
	Quantity per Roll	2500
	Unit Price	\$0.20/Label
	Trade Name	UltraTemp®
	Brand Name	Brady®
	Country of Origin 	Mexico
	HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
	ECCN (Export Commodity Control Number) 	EAR99

Dimensions	Dimensions	0.5 in H x 1 in W
	Height	0.5 in
	Width	1 in
	Label/Tape Size	0.5 in H x 1 in W
	Printable Area Dimensions	0.50 in H x 1.00 in W
	Printable Area Height	0.50 in
	Printable Area Width	1.00 in
	Thickness	0.0044 in

Material Characteristics	Vertical Repeat	0.6 in
	Web Width	1.2 in
	Material Number 	B-727
	Material 	Polyimide
	Material Properties	Harsh Flux Wash-resistant
	Label Properties	Heat Resistant, Permanent Adhesive
	Adhesive Type	Permanent Acrylic
	Finish	Gloss
	Color	White
	Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Wave Solder-Resistant
	Indoor or Outdoor Use	Indoor Use
	Service Temperature Range °F	-94 °F - 572 °F
	Minimum Service Temperature °F	-94 °F
	Minimum Service Temperature °F	-94 °F
	Maximum Service Temperature °F	572 °F
	Compatible Surface Types	High Surface Energy

Product Features	Application 	Circuit Board Labeling, Component and Equipment Labeling, Temperature Indicating Labeling
	Shape	Rectangle
	Average Outdoor Durability 	Not Recommended
	Corner Type	Rounded Corners
	Label/Media Format	Roll
	Quantity per Row	1

Printing Specifications	Print Technology	Thermal Transfer
Compatibility	Printer Compatibility	BBP33, i3300, i5300
	Recommended Ribbon 	B30-R6000
	Suggested Ribbon Series	R6000 Halogen Free
Compliance	UNSPSC 	55121612
	RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863