

Specifications

Key Characteristics

Product Number	153425
UPC	888434564288
UOM	Roll of 20000 Labels
Quantity per Roll	20000
Unit Price	\$0.01/Label
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.25 in H x 0.25 in W
Height	0.25 in
Width	0.25 in
Label/Tape Size	0.25 in H x 0.25 in W
Thickness	0.0034 in
Horizontal Repeat	0.32 in
Vertical Repeat	0.35 in
Web Width	2.37 in
Core Diameter	2 in

Material Characteristics

Material Number 	B-473 (View Technical Data Sheet)
Material 	Static Dissipative Polyester
Material Properties	Static-dissipative
Label Properties	Harsh Environment, Heat Resistant, Permanent Adhesive
Adhesive Type	Static Dissipative Permanent Acrylic
Finish	Gloss
Color	White
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, UV-Resistant, Weather-Resistant
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-40 °F - 356 °F

Minimum Service Temperature °F	-40 °F
Maximum Service Temperature °F	356 °F
Compatible Surface Types	High Surface Energy

Product Features

Application 	Circuit Board Labeling, Electrical Labeling, General Identification
Shape	Rectangle
Corner Type	Rounded Corners
Quantity per Row	7

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP33, i3300, i5300
Recommended Ribbon 	B30-R6000

Compliance

UNSPSC 	55121612
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863