


## Specifications



### Key Characteristics


Catalog Page # 	65
Product Number	140935
UPC	754473941673
Applications 	Cable & Wire Marking
UOM	Roll of 150 Each
Quantity per Roll	150
Unit Price	\$2.27/Sleeve
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

### Dimensions


Dimensions	1.66 in H x 2 in W
Height	1.66 in
Width	2 in
Roll Width	2 in
Sleeve Size	1 in Dia x 2 in W
Sleeve Width	2 in
Vertical Repeat	2 in
Recovered Diameter	0.5 in
Recovered Wall Thickness	0.036 in
Web Width	3.49 in
Diameter as Supplied	1 in

### Material Characteristics

Material Number 	<a href="#">B-7641 (View Technical Data Sheet)</a>
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable, Low-smoke, Zero-halogen
Label Properties	Heat Shrink
Finish	Matte

Color	White
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Self-Extinguishing, UV-Resistant, Weather-Resistant
Shrink Ratio 	2:1
Service Temperature Range °F	-67 °F - 221 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	221 °F



## Product Features

Application 	Electrical Labeling, Wire and Cable Labeling
Label/Media Format	Roll
Printable Sides	Double-Side Printable
Quantity per Row	1
Sleeve Slits	No


## Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

## Compatibility

Printer Compatibility	BBP33, i3300, i5300
Recommended Ribbon 	B30-R6000
Suggested Ribbon Series	R6000 Halogen Free, R6600
Wire Diameter Range	0.5 in to 0.95 in
Wire Gauge Range 	00 AWG - 500 MCM

## Compliance

UNSPSC 	39131502
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863