


Specifications



Key Characteristics


Catalog Page # 	64
Product Number	142984
UPC	662820968245
Applications 	Cable & Wire Marking
UOM	Roll of 250 Each
Quantity per Roll	250
Unit Price	\$4.64/Sleeve
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions



Dimensions	1.25 in H x 2 in W
Height	1.25 in
Width	2 in
Roll Width	2 in
Sleeve Size	0.75 in Dia x 2 in W
Sleeve Width	2 in
Vertical Repeat	1.625 in
Recovered Diameter	0.375 in
Recovered Wall Thickness	0.025 in
Web Width	3.49 in
Diameter as Supplied	0.75 in

Material Characteristics

Material Number 	B-345 (View Technical Data Sheet)
Material 	High Temperature Heat-shrink Polyvinylidene Fluoride Sleeve
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte

Color	Black
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, High Temperature-resistant, Humidity-Resistant, UV-Resistant, Weather-Resistant
Shrink Ratio 	2:1 (3:1 for 0.094" Dia)
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-67 °F - 437 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	437 °F



Product Features

Application 	Electrical Labeling, Temperature Indicating Labeling, Wire and Cable Labeling
Average Outdoor Durability 	2 Years
Label/Media Format	Roll
Printable Sides	Double-Side Printable
Quantity per Row	1
Sleeve Slits	No

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP33, i3300, i5300
Recommended Ribbon 	B30-R4400-WT
Suggested Ribbon Series	R4400W, R6800
Wire Diameter Range	0.375 in to 0.7 in
Wire Gauge Range 	2 AWG - 0000 AWG

Compliance

UNSPSC 	39131502
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863