

## Specifications

|                     |  |                          |
|---------------------|--|--------------------------|
| Key Characteristics | Product Number   | 170985                   |
|                     | UPC  | 888434620717             |
|                     | UOM  | Roll of 4000 Labels      |
|                     | Quantity per Roll                                      | 4000                     |
|                     | Unit Price   | \$0.07/Label             |
|                     | Trade Name   | Wraprot™ A6200           |
|                     | Brand Name   | Brady®                   |
|                     | <a href="#">Country of Origin</a>                      | United States of America |
|                     | <a href="#">HTS Code (Harmonized Tariff Schedule)</a>  | 8443.99.2550             |
|                     | <a href="#">ECCN (Export Commodity Control Number)</a> | EAR99                    |
| Dimensions          | Dimensions   | 1.25 in H x 0.5 in W     |
|                     | Height   | 1.25 in                  |
|                     | Width  | 0.5 in                   |
|                     | Label/Tape Size  | 1.25 in H x 0.5 in W     |
|                     | <a href="#">Printable Area Dimensions</a>              | 0.375 in H x 0.5 in W    |
|                     | Printable Area Height                                  | 0.375 in                 |
|                     | Printable Area Width                                   | 0.5 in                   |
|                     | Thickness  | 0.004 in                 |
|                     | Vertical Repeat  | 1.375 in                 |

|                          |                                 |   |
|--------------------------|---------------------------------|---|
|                          | Web Width                       | 1.312 in  |
|                          | Core Diameter                   | 1 in  |
| Material Characteristics | <a href="#">Material Number</a> | <a href="#">B-417 (View Technical Data Sheet)</a>           |
|                          | <a href="#">Material</a>        | Self-laminating Vinyl                                       |
|                          | Material Properties             | Self-extinguishing, Self-laminating                         |
|                          | Label Properties                | Aggressive Adhesive, Self Laminating & Wrap A               |
|                          | Adhesive Type                   | Permanent Acrylic   |
|                          | Finish                          | Matte   |
|                          | Color                           | Clear, White  |
|                          | Resistance Properties           | Abrasion-resistant, Chemical-resistant, Humidi<br>resistant |
|                          | Indoor or Outdoor Use           | Indoor/Outdoor Use  |
|                          | Service Temperature Range °F    | -40 °F - 158 °F   |
|                          | Minimum Service Temperature °F  | -40 °F  |
|                          | Maximum Service Temperature °F  | 158 °F  |
|                          | Compatible Surface Types        | Curved  |
| Product Features         | <a href="#">Application</a>     | Data and Telecommunications Labeling, Electr                |
|                          | Shape                           | Rectangle   |
|                          | Corner Type                     | Rounded Corners   |
|                          | Quantity per Row                | 1   |

|                         |                                    |  |
|-------------------------|------------------------------------|--|
| Printing Specifications | Print Technology                   | Thermal Transfer                                   |
| Compatibility           | Printer Compatibility              | Wraptor A6200                                      |
|                         | <a href="#">Recommended Ribbon</a> | A62-R4300  |
|                         | Wire Diameter Range                | 0.12 in to 0.24 in                                 |
|                         | <a href="#">Wire Gauge Range</a>   | 12 AWG - 6 AWG                                     |
| Compliance              | <a href="#">UNSPSC</a>             | 55121606   |
|                         | RoHS Compliance Status             | Compliant with Directive 2011/65/EU and 2002/95/EC |