






Specifications


Key Characteristics


| | |
|--|--|
| Catalog Page #  | 147 |
| Product Number | 150908 |
| UPC | 754473631260 |
| Applications  | Arc Flash Labels, Arrow Tape, Pipe & Valve Marking, Safety & Compliance ID, Visual Workplace Labeling, Warehouse Marking |
| UOM | Roll of 50 Feet |
| Brand Name | Brady® |
| Country of Origin  | Mexico |
| HTS Code (Harmonized Tariff Schedule)  | 8443.99.2550 |
| ECCN (Export Commodity Control Number)  | EAR99 |

Dimensions



| | |
|-----------------|--------------------|
| Label/Tape Size | 0.5 in W x 50 ft L |
| Roll Length | 50 ft |
| Roll Width | 0.5 in |
| Thickness | 0.004 in |
| Web Width | 2.5 in |

Material Characteristics

| | |
|---|---|
| Material Number  | B-595 (View Technical Data Sheet) |
|---|---|

| | |
|---|---|
| Material  | Vinyl |
| Label Properties | Aggressive Adhesive, Harsh Environment, Outdoor Durable, Permanent Adhesive |
| Adhesive Type | Permanent Acrylic |
| Finish | Gloss |
| Color | Yellow |
| Resistance Properties | Abrasion-Resistant, Chemical-Resistant, Oil-Resistant, Water-Resistant |
| Indoor or Outdoor Use | Outdoor Use |
| Service Temperature Range °F | -40 °F - 180 °F |
| Minimum Service Temperature °F | -40 °F |
| Minimum Service Temperature °F | -40 °F |
| Maximum Service Temperature °F | 180 °F |
| Minimum Application Temperature °F | 0 °F |
| Compatible Surface Types | General |


Product Features

| | |
|--|---|
| Application  | Component and Equipment Labeling, Electrical Labeling, Facility Identification, Floor Marking, Laboratory Labeling, Lean and 5S Labeling, Pipe and Valve Marking, Warehouse Marking |
| Average Outdoor Durability  | 8 to 10 Years |
| Label/Media Format | Roll |
| Quantity per Row | 1 |



Printing Specifications

| | |
|------------------|------------------|
| Print Technology | Thermal Transfer |
|------------------|------------------|

Compatibility

| | |
|--|-------------|
| Printer Compatibility | BMP61, M611 |
| Recommended Ribbon  | M61-R10010 |
| Suggested Ribbon Series | R10000 |

Compliance

| | |
|--|--|
| UNSPSC  | 55121612 |
| California Prop 65  | Due to inconclusive data, this product may not ship to California at this time |
| RoHS Compliance Status | Please contact our CS department for more information |