

Specifications

Key Characteristics

Catalog Page # 	165
Product Number	114941
UPC	662820926924
Applications 	Cable & Wire Marking, Panel Labeling
UOM	Roll of 100 Each
Quantity per Roll	100
Unit Price	\$0.77/Sleeve
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.235 in H x 1.75 in W
Height	0.235 in
Width	1.75 in
Roll Width	1.75 in
Sleeve Size	0.125 in Dia x 1.75 in W
Sleeve Width	1.75 in

Vertical Repeat	0.75 in
Recovered Diameter	0.046 in
Recovered Wall Thickness	0.02 in
Web Width	2.25 in
Diameter as Supplied	0.125 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	White
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant
Shrink Ratio 	3:1
Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	275 °F

Product Features

Application 	Electrical Labeling, Wire and Cable Labeling
Label/Media Format	Roll

Printable Sides	Single-Side Printable
Quantity per Row	1
Sleeve Slits	No

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BMP71
Recommended Ribbon 	M71-R4300
Suggested Ribbon Series	R4300, R6600
Wire Diameter Range	0.046 in to 0.11 in
Wire Gauge Range 	22 AWG - 16 AWG

Compliance

UNSPSC 	39131502
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information