





Specifications

Key Characteristics



Catalog Page # 	158
Product Number	115052
UPC	662820928034
Applications 	General & Industrial ID, Panel Labeling
UOM	Box of 100 Labels
Quantity per Roll	100
Unit Price	\$0.00/Label
Trade Name	BMP®71
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550

Dimensions



Dimensions	1.8 in H x 1.8 in W
Height	1.8 in
Width	1.8 in
Label/Tape Size	1.8 in H x 1.8 in W
Thickness	0.0256 in
Vertical Repeat	2.625 in
Web Width	2.25 in
Inside Diameter	1.2 in

Hole Inside Diameter	1.2 in
----------------------	--------

Material Characteristics

Material Number 	B-593 (View Technical Data Sheet)
Material 	Polyester
Material Properties	Raised
Label Properties	Heat Resistant, Permanent Adhesive
Adhesive Type	Permanent Acrylic - Foam Backed
Finish	Gloss
Color	Black
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant
Indoor or Outdoor Use	Outdoor Use
Service Temperature Range °F	-4 °F - 212 °F
Minimum Service Temperature °F	-4 °F
Minimum Service Temperature °F	-4 °F
Maximum Service Temperature °F	212 °F
Compatible Surface Types	High Surface Energy

Product Features


Application 	Electrical Labeling, General Identification
Shape	Square
Average Outdoor Durability 	3 to 5 Years
Corner Type	Rounded Corners

Label/Media Format	Box
Quantity per Row	1

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------



Compatibility

Printer Compatibility	BMP71
Recommended Ribbon 	M71-R4400-WT
Suggested Ribbon Series	R4400, R6900

Preprinted Information

Pre-Printed Areas on Label	Colored Write-On Area
----------------------------	-----------------------

Compliance

UNSPSC 	55121612
California Prop 65 	Due to inconclusive data, this product may not ship to California at this time
RoHS Compliance Status	Please contact our CS department for more information