

Specifications

Key Characteristics

Catalog Page # 	112
Product Number	143223
UPC	754473082871
Applications 	Cable & Wire Marking, Panel Labeling
UOM	Cartridge of 7 Feet
Quantity per Row	1
Trade Name	PermaSleeve®
Brand Name	Brady®
Ribbon Series	R4300
Country of Origin 	Mexico
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.235 in H
Height	0.235 in
Roll Length	7 ft
Sleeve Size	0.125 in Dia x 7 ft L
Recovered Diameter	0.47 in
Web Width	0.813 in
Diameter as Supplied	0.125 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	Black on White
Ribbon Color	Black
Tape Color	White
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant

Shrink Ratio 	3:1
Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	275 °F

Product Features

Application 	Electrical Labeling, Wire and Cable Labeling
Label/Media Format	Label/Media in Cartridge with Ribbon

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BMP41, BMP51, BMP53
Wire Diameter Range	0.046 in to 0.11 in
Wire Gauge Range 	22 AWG - 16 AWG

Compliance

UNSPSC 	39131502
California Prop 65 	 WARNING: Cancer - www.p65warnings.ca.gov
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863