

Specifications

Key Characteristics

Catalog Page # 	198
Product Number	133106
UPC	754473897673
Applications 	Cable & Wire Marking
UOM	Roll of 50 Feet
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	2.43 in H
Height	2.43 in
Roll Length	50 ft
Sleeve Size	1.5 in Dia x 50 ft L
Recovered Diameter	0.5 in
Recovered Wall Thickness	0.035 in
Diameter as Supplied	1.5 in
Core Diameter	1.625 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	Yellow
Resistance Properties	Chemical-Resistant, Smear-Resistant
Shrink Ratio 	3:1
Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F

Minimum Service Temperature °F	-67 °F
Maximum Service Temperature °F	275 °F

Product Features

Application 	Wire and Cable Labeling
Label/Media Format	Roll
Printable Sides	Single-Side Printable

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP72, i5100, i7100, THT 3" Core Printers
Recommended Ribbon 	IP-R6600, R6600
Suggested Ribbon Series	R4300, R5000, R6600
Wire Diameter Range	0.5 in to 1.45 in

Compliance

UNSPSC 	39131502
California Prop 65 	 WARNING: Cancer - www.p65warnings.ca.gov
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863