

Specifications

Key Characteristics

Product Number	132777
UPC	754473855871
Applications 	Cable & Wire Marking
UOM	Roll of 50 Feet
Trade Name	PermaSleeve®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions

Dimensions	0.851 in H
Height	0.851 in
Roll Length	50 ft
Sleeve Size	0.5 in Dia x 50 ft L
Recovered Diameter	0.187 in
Recovered Wall Thickness	0.025 in
Diameter as Supplied	0.5 in
Core Diameter	1.625 in

Material Characteristics

Material Number 	B-342 (View Technical Data Sheet)
Material 	Heat-shrink Polyolefin
Material Properties	Flame-retardant, Heat-shrinkable
Label Properties	Heat Shrink
Finish	Matte
Color	White
Resistance Properties	Chemical-Resistant, Smear-Resistant
Shrink Ratio 	3:1
Service Temperature Range °F	-67 °F - 275 °F
Minimum Service Temperature °F	-67 °F
Minimum Service Temperature °F	-67 °F

Maximum Service Temperature °F	275 °F
--------------------------------	--------

Product Features

Application 	Wire and Cable Labeling
Label/Media Format	Roll
Printable Sides	Single-Side Printable

Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP12, BBP72, i5100, i7100, IP Series, PR Plus, THT 3" Core Printers
Recommended Ribbon 	IP-R6606, R6606
Suggested Ribbon Series	R4300, R5000, R6600
Wire Diameter Range	0.187 in to 0.45 in
Wire Gauge Range 	8 AWG - 1 AWG

Compliance

UNSPSC 	39131502
California Prop 65 	 WARNING: Cancer - www.p65warnings.ca.gov
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863