

Technical Information

Brand: Brady

Product Type: Thermal Transfer Label

Color: White/Transparent

Primary Color: White/Clear

Maximum Service Temperature: +158°F

Minimum Service Temperature: -40°F

Thickness: 0.004in

Resistance Properties: Chemical Resistant; Humidity Resistant; Oil Resistant; Water Resistant; Weather Resistant

Finish: Matte

Adhesive Type: Permanent Acrylic

Printer Compatibility: Brady 1244, Brady 1344, Brady 2461, Brady 3481, Brady 6441, Brady 300MVP Plus, Brady 200MVP Plus, Brady 300X-Plus II, Brady 360X-Plus II, Brady 600X-Plus II, Tagus T200, Tagus T300, Thermal Transfer Printer, IP300, IP600, BBP®81

Recommended Ribbon Series: R4300; R4500

Length: 0.75in

Material: Vinyl

Material Category: Plastic

Width: 1in

Shape: Rectangular

Applications: Wire and Cable Identification

Quantity per Roll: 5000

Standards Met: ASTM D 1000, ASTM D 2979, ASTM G155, PSTC-7, UL Recognized to UL Listed 969 Labeling/Marking Standard, UL Listed File No. MH17154, RoHS Compliant to 2005/618/EC MCV, RoHS Compliant 2002/95/EC

Availability: In Stock

Availability: In Stock

Storage Conditions: Ambient

Weight: 1.538

Country Of Origin: US