






Specifications



Key Characteristics

Catalog Page # 	159
Product Number	139551
UPC	754473928643
Applications 	General & Industrial ID
UOM	Roll of 1000 Labels
Quantity per Roll	1000
Unit Price	\$0.20/Label
Trade Name	CleanLift®
Brand Name	Brady®
Country of Origin 	United States of America
HTS Code (Harmonized Tariff Schedule) 	8443.99.2550
ECCN (Export Commodity Control Number) 	EAR99

Dimensions


Dimensions	2 in H x 3 in W
Height	2 in
Width	3 in
Label/Tape Size	2 in H x 3 in W
Thickness	0.003 in
Vertical Repeat	2.125 in
Web Width	3.2 in
Core Diameter	3 in

Material Characteristics

Material Number 	B-533 (View Technical Data Sheet)
Material 	Polyester
Label Properties	Heat Resistant, Removable
Adhesive Type	Removable Acrylic
Finish	Gloss
Color	White
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Humidity-Resistant, Low Temperature-Resistant, Solvent-Resistant, Weather-Resistant
Indoor or Outdoor Use	Outdoor Use

Service Temperature Range °F	-94 °F - 212 °F
Minimum Service Temperature °F	-94 °F
Minimum Service Temperature °F	-94 °F
Maximum Service Temperature °F	212 °F
Compatible Surface Types	General


Product Features

Application 	Circuit Board Labeling, General Identification, Laboratory Labeling
Shape	Rectangle
Corner Type	Rounded Corners
Label/Media Format	Roll
Quantity per Row	1


Printing Specifications

Print Technology	Thermal Transfer
------------------	------------------

Compatibility

Printer Compatibility	BBP81, i5100, i7100, IP Series, PR Plus, THT 3" Core Printers
Recommended Ribbon 	IP-R6002, R6002
Suggested Ribbon Series	R6000 Halogen Free

Compliance

UNSPSC 	55121612
RoHS Compliance Status	Compliant with Directive 2011/65/EU and 2015/863