BRETFORD BASICS™ UNIVERSAL LARGE FLAT PANEL MONITOR CART

FPP72 Features a universal mounting arm that is adjustable to fit most large flat panel monitors from 42" to 61".



6

FPP72V200 Features a universal mounting arm for most smaller flat panel monitors from 30" to 52" diagonal.









FEATURES

- A cost effective and stylish method of displaying a flat panel monitor between rooms, high traffic locations, and events. Provides the basic platform for applications where just the monitor is in use or add on accessories to build a multimedia platform to meet your individual needs for presentations and displays using computers, DVD players, wireless devices, etc.
- FPP72 features an adjustable mounting arms are geared to be width and height adjustable to fit the mounting hole pattern on most larger flat panel monitors 42" to 61" diagonal up to 170 lbs. and with a mounting hole pattern 400mm wide by 200mm high or greater. Optional arm extionsion kit FPLM-ARM9 available for larger hole patterns.
- FPP72V200 features adjustable mounting arms for most smaller flat panel monitors 30" to 52" diagonal up to 170 lbs. and with a mounting hole pattern no larger than 700mm wide by 400mm high.
- The FPP72 with adjustable arms may be easily rotated with the touch of a finger to use the monitor in landscape to portrait format and features a 0°-15° forward tilt adjustment.
- The FPP72V200 features a 0°-15° forward tilt adjustment and only mounts in landscape format.
- Sturdy aluminum pole is 72"H and features adjustment holes, spaced 1" apart, and span the entire length for height adjustment of the monitor and to allow the addition of accessory shelving, cord bins, and CPU tower holder.
- Vertical pole features cord management channels in the front and back and adjustable cord management clips to keep power and data cables neat. K-base
 design includes 4" casters with locking brakes and features flex adjustment to provide a stable platform by keeping all four casters in constant contact with the
 floor on uneven surfaces.
- FPP72 series carts feature an extruded aluminum pole which has an average of 90% post-consumer recycled content and cast aluminum base and mount with an average of 30% post-consumer recycled content. Model FPP72V200 has a steel mount with 25%-35% post-consumer recycled content. All aluminum and steel components are recyclable at the end of the product life cycle. FPP72 series carts are certified to GREENGUARD Gold standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.



5

FPP72 MOUNTING ARM ADJUSTABLE DIMS

Width = 310mm (12.2") - 825 mm (23.48") Height = 176mm (6.93") - 683mm (26.89")

FPP72V200 MOUNTING ARM ADJUSTABLE DIMS

Width = 100mm (3.94") - 700mm (27.56") Height = 100mm (3.94") - 400mm (15.75")

OVERALL DIMENSIONS

48"w x 80"h x 28"d

CARTON DIMS, WEIGHT & FREIGHT CLASS

FPP72: 94 lbs total, Freight class 70

#1 - FPCUVMNT1 - 31-1/2"l x 9"d x 7-1/2"h, 20 lbs

#2 - FPP72 KBASE - 54"I x 37"d x 10"h, 56 lbs

#3 - FPCMPOLE72 - 77"I x 5"d x 5"h, 18 lbs

Ship ready to assemble in three (3) carton packs

FPP72V200: 93 lbs total, Freight class 70

#1 - FPP72V200 KBASE - 54"I x 37"d x 10"h, 75 lbs

#2 - FPCMPOLE72 - 77"I x 5"d x 5"h, 18 lbs

Ship ready to assemble in two (2) carton packs

FPP72 CARTON UPC CODES

FPP72:

#1 - FPCUVMNT1 (mounting arms) - 0 96633 26856 6

#2 - FPP72 KBASE (base) - 0 96633 26903 7

#3 - FPCMPOLE72 (vertical pole) - 0 96633 26810 8

FPP72V200:

#1 - FPP72V200 KBASE (base & mounting arms) - 0 96633 28969 1

#3 - FPCMPOLE72 (vertical pole) - 0 96633 26810 8

FPP72 ACCESSORIES, COLOR & UPC CODES

FPPSHX-469 - Large Accessory Shelf, Dark Gray - 0 96633 26921 1 FPPCB - Cable Bin w/Electrical Unit, Aluminum - 0 96633 26884 9 FPPCPU - CPU Harness, Aluminum - 0 96633 26885 6

ENVIRONMENTAL SPECIFICATIONS

The FPP72 series carts are constructed with an extruded aluminum which has an average of 90% post-consumer recycled content and aluminum cast base and mount with an average of 30% post-consumer recycled content. Model FPP72V200 has a steel mount with 25% to 35% post-consumer recycled content. All aluminum and steel components are recyclable at the end of the product life cycle. FPP72 series carts are certified to GREENGUARD Indoor Air Quality standards.

FPP72 SUGGESTED SPECIFICATIONS

The FPP72 has an adjustable mounting arm assembly, constructed from cast aluminum and is 176mm to 683mm height and 310mm to 825mm width adjustable to fit the mounting holes of most large flat panel monitors, 42" to 61" diagonal or 170 lbs. The monitor should be mounted on the pole so that the top of the monitor does not extend above the top of the pole. A kit including several sizes of spacers, washers, and bolts is included to fit the mounting assembly to the back panel of most monitors. Additional hardware may need to be purchased at your local hardware store. The monitor and accessories attach to the vertical pole using a mounting spike which clips into place and secures using two 3/16" hex head screws. The vertical pole is 72"I and constructed from extruded aluminum with multiple mounting holes spaces, 1" apart, the entire length of the pole. The vertical pole attaches to the base using one 1/2" hex head center bolt and four 3/16" hex head corner bolts. The base is constructed of cast aluminum and pre-assembled in a K pattern with four 4" twin wheel casters, each with a locking brake. The base features flexible legs that constantly adjust to keep all four casters in contact with uneven floors. Ships in three boxes via LTL truck.

FPP72V200 SUGGESTED SPECIFICATIONS

The FPP72V200 has adjustable mounting arms and is 100mm to 400mm height and 100mm to 700mm width adjustable to fit the mounting holes of most smaller flat panel monitors, 30" to 52" diagonal or 170 lbs. The monitor should be mounted on the pole so that the top of the monitor does not extend above the top of the pole. A kit including several sizes of spacers, washers, and bolts is included to fit the mounting assembly to the back panel of most monitors. Additional hardware may need to be purchased at your local hardware store. The monitor and accessories attach to the vertical pole using a mounting nugget that bolts into place and features a transition plate that supports an adjustable mounting device. The vertical pole is 72"l and constructed from extruded aluminum with multiple mounting holes spaces, 1" apart, the entire length of the pole. The vertical pole attaches to the base using one 1/2" hex head center bolt and four 3/16" hex head corner bolts. The base is constructed of cast aluminum and pre-assembled in a K pattern with four 4" twin wheel casters, each with a locking brake. The base features flexible legs that constantly adjust to keep all four casters in contact with uneven floors. Ships in two boxes via LTL truck.



5