

# PureCharge Cart<sup>®</sup> 20 & 40

## For iPad

Ready-to-go charging for Apple iPad devices. Each cart arrives with pre-installed Lightning cables, reducing setup time so you can focus on device deployment for your business or school.





## **OPTIMIZED FOR APPLE**

Pre-wired with custom Lightning cables that are optimal length for each slot with right-angled connector that makes it easy to connect devices.



## **READY TO USE**

The PureCharge Cart<sup>®</sup> comes fully assembled ready to load.



## SIZE MATTERS

Designed to optimize space, the PureCharge Cart<sup>®</sup> maneuvers easily though standard doorways and can charge up to 40 iPad devices at once.



# **BUILT TO LAST**

Each unit is fully welded. Designed and built in the USA.



### **OPTIMIZED FOR iOS AND iPadOS DEVICES**



**SIMULTANEOUS CHARGING** | Provides up to 2.4A simultaneously to each connected device.



**SECURITY** | 3-point locking system with programmable combination lock.



**STATUS ON DEMAND** | LED lights positioned over each device let users know when devices are fully charged and ready for use.



**INDUSTRIAL GRADE** | 5 in. wheels with both brake and directional locking casters for maximum maneuverability.



**ERGONOMIC DESIGN** | Features built in handles on both sides of cart and rubberized table-top surface for extra space.

### SPECIFICATIONS

#### Construction

USA-sourced steel Manufactured in Franklin Park, IL

Device Compatibility iPad (all models with lightning); iPad models with USB-C (require USB-A to C cable packs, sold separately: HNQ52)

Power (HGFM2) AC: 10A Max. Draw DC: up to 2.4A to each device

Power (HGFN2) AC: 5A Max. Draw DC: up to 2.4A to each device

#### Shipment Includes:

- PureCharge Cart<sup>®</sup> - Ships fully assembled
- Lightning to USB cables (preinstalled)
- User-programmable combination lock
- Wall-mountable locking system for securing cart in a room
- Power cord (preinstalled)

Safety

## DIMENSIONS

	HGFN2	HGFM2
DEVICE CAPACITY	20	40
CART DIMENSIONS	36.3 x 21.8 x 38.2 in.	
SLOT DIMENSIONS	Minimum 1 in. width with reconfigurable dividers	
WEIGHT	146 lbs.	154 lbs.

DIMENSIONS ARE EXPRESSED WIDTH X DEPTH X HEIGHT