

AMPLIFIED TRUMPET SPEAKERS

Music and Paging | Model AMP04TRP



Ceiling Mounted



Pole Mounted



Wall Mounted



- Capable of Powering up to 4 Trumpets (One Amplified and Three Non-amplified Trumpets)
- Utilizes a Noise Cancelling Balance Input
- 4" Full Range Driver
- 1 Year Warranty
- 12V Power Supply Included
- Frequency:
 - 140 Hz-20 kHz (music)
 - 250 Hz- 3 kHz (paging)
- Dispersion: 120°H x 90°V
- Dimensions: 5.9H x 9.8W x 10D inches
- Unique "C" Mounting Bracket
- 60 Foot Throw
- Weatherized
- Paintable White or Black
- Ceiling, Pole and Wall Mountable



205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Amplified Trumpet Speakers

AMP04TRP



AMP 04TRP - Amplifier

POWER	25 Watts
FREQUENCY RESPONSE	20 Hz to 30kHz +0-2dB
NOISE FLOOR	Better than 90 dB
DISTORTION	Better than .1% at 10 Watts
INPUT	Line Input -10 to +4dB
INPUT CONFIGURATION	Differential, Balanced and DC Isolated
VOLUME CONTROL	Step for Mechanical Level Memory
PROTECTION	Short Circuit, Heat and Over Current
MAX POWER SUPPLY WIRE LENGTH	400 Ft. with 16 Gauge Wire
COLOR	White
MULTIPLE AMPLIFIERS	Yes, Line Input in Parallel
EACH AMPLIFIER MAY POWER	Four Speaker Total per Amp
INPUT / OUTPUT	Each Amp has a Line Level Input and Output
CONNECTOR TYPE	Phoenix Connector
CONDUIT ENTRY	Two 1/2" Conduit Access Holes with Knock Outs
TYPICAL LINE LEVEL SOURCES	CD Player, Audio Mixer, Background Music Service, Telephone PBX Dry Audio Pair
	Hooked to the Balanced +/- Input. There is No Shield on a Telephone Input.
HOOK UP FOR ADDITIONAL HORNS	Wired through the Conduit Entry, Use the 4 Way Binding Posts for Additional High Level Speakers Hooked up to the Amplifier.
FOR FOUR HORNS	Wire them Series Parallel to Achieve a 4 Ohm Load Impedance
POWER SUPPLY	12 Volts UL listed
WARRANTY	1 Year

04TRP - Speaker

SYSTEM TYPE	Full Range
SPEAKER DRIVER	4" Polypropylene Coated
OUTDOOR / INDOOR	Yes
FREQUENCY RESPONSE	
MUSIC	140 Hz-20 kHz
SPEECH	250 Hz - 3 kHz
CROSSOVER	4kHz
IMPEDANCE	4 Ohms
SENSITIVITY (1W, 1M)	90 dB
POWER HANDLING	80 Watts Max
	40 Watts RMS
DISPERSION COVERAGE	120° H x 90°V
ENCLOSURE	ABS Plastic
GRILL	Aluminum
OPERATING TEMP.	14°F to 176°F
	(-10°C to 80°C)
DIMENSIONS: HWD	5.9"H x 9.8" W x 10"D
PRODUCT WEIGHT	4.98 Lbs. (2.26 kg)
THROW (DISTANCE)	60 Feet
COLOR	Paintable White or black
MOUNTING HARDWARE	Unique "C" Bracket
	(Included)
TERMINAL COVER PLATE	(Included)
SECURITY CABLE	(Included)
WARRANTY	5 Years



AMPTRP Back Plate



Options available:

- Silencer AMP-MOVC (Mono Volume Control)
- Silencer AMP-STVC (Stereo Volume Control)