

P8378P

PATIO BLASTER P SERIES SPEAKERS



- 70/100 Volts & 8 ohms
- 8", 3-Way, Ported
- 80 Watts RMS Maximum Power
- 5, 10, 20, 40 Watts
- Outdoor/Indoor
- Weatherized Aluminum Grill and Bracket
 - Black and White Colors Available
 - "U" Mount Bracket Included
 - Ceiling or Wall Mount Possibilities
 - 5", 6" Available



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

P8378P

ARCHITECTS AND ENGINEERS
SPECIFICATIONS/TECHNICAL DATA

PATIO BLASTER P SERIES



P8378: 8"



P6278: 6"



P5278: 5"

GENERAL SPECIFICATIONS:

MODEL NUMBER:	P8378P
DESCRIPTION:	8", 3-Way, ported
OUTDOOR:	YES
IMPEDANCE:	70/100 Volts & 8 Ohms
DISPERSION:	85°
SENSITIVITY (1W/1M):	89 dB +/- 3dB
MAX POWER:	80 Watts
NOMINAL POWER:	5, 10, 20, 40 Watts
FREQUENCY RESPONSE:	50 Hz - 20 kHz
CROSS OVER:	4 kHz
HIGH FREQUENCY DRIVER:	25mm Silk
MIDRANGE FREQUENCY:	2", Titanium
LOW FREQUENCY DRIVER:	8", Polypropylene/Rubber
WOOFER SIZE:	8"
WOOFER MATERIAL:	Polypropylene/Rubber
MIDRANGE/S:	1 Each
MIDRANGE SIZE:	2"
MIDRANGE MATERIAL:	Titanium
TWEETER/S:	1 Each
TWEETER SIZE:	25 mm
TWEETER MATERIAL:	Silk
GRILL MATERIAL:	Aluminum
ENCLOSURE:	Plastic
DIMENSIONS: (LxWxH/inches):	12 ^{1/8"} x 10 ^{1/2"} x 14 ^{1/8"}
WEIGHT (pounds):	17.2 lbs.
COLOR/S:	Black, White
PAINTABLE:	YES

ACCESSORIES:

• SS-36	In Ground Stainless Steel Stake (36")
• OWI1070M	Attenuator, Mono, 70V, 10W Max
• OWI3570M	Attenuator, Mono, 70V, 35W Max
• OWI7570M	Attenuator, Mono, 70V, 75W Max
• OWI2570S	Attenuator, Stereo, 70V, 25W Max

