

## Full Cycle Ratchet Tool, Dieless Installs Service Entrance Splice Connectors #10 - 1/0 Str.

### Full Cycle Ratchet Tool, Dieless

Installs Service Entrance Splice Connectors #10 to 1/0 Str.

**Tool:** OH25

- Ratchet mechanism does not allow handles to open until full cycle is complete
- Easy, one-hand operation incrementally closes jaws with each handle stroke
- Spring-loaded comfort grip handles
- Forged steel jaws and stainless steel indenter

### For Use On:

**Conductor Range: #10 - 1/0 Str.**

5/8" Service Entrance Sleeves:

INSULINK™ Type ES (insulated) #10 - 1/0 Str.

LINKIT™ Type YSU (bare) #8 - 1/0 Str.

5/8" Neutral Tension Sleeves

HYSPLICE™ Types:

YS-S, YCS-R, YDS-AT #4 - 1/0 Str.

HYPLUG™ AYP Type #6 - 1/0 Str.



### Models:

OH25

Tool, #10 - 1/0 Str

### Specifications:

|                         |                         |
|-------------------------|-------------------------|
| <b>Handle Force:</b>    | 50 lbs max.             |
| <b>Force Developed:</b> | 6,000 lbs max.          |
| <b>Size:</b>            | 12.25" x 3.75" x 1.50"  |
| <b>Weight:</b>          | 2 lbs. 11 oz.           |
| <b>Die Style:</b>       | Dieless                 |
| <b>Warranty:</b>        | 5 year limited warranty |

### Accessories:

PT8504:

Go/No-Go Gauge; used to check crimp dimensions