4.5 Ton, 6,000 PSI, Remote C-Head

Remote Operated Hydraulic Tool

Y29BH Tool:

- D series nest dies and Y29 series indenter dies
- Light weight, portable design
- C-shaped head; 1.2" jaw opening
- Easy placement/removal on continuous conductor lengths

For Use On:

Copper #8 - 2/0 AWG Code/Flex

Nylon Insulated Lugs:

(Connectors meet MIL-T-7928 requirements) YAEV-L, YAEV-H, YAEV-RS, YAEV-RH

Non-Insulated Lugs:

(Connectors meet MIL-T-7928 requirements) YAV-L, YAV-R, YAV-RS

Copper #8 - 4/0 AWG

Non-Insulated Splices: (Type YSV-L connectors UL Listed/CSA Certified)

YSM, YSV-L

Installation Die Chart for Y29BH (Connectors meet MIL-T-7928 requirements)

Non-Insulated Connectors		Maximum Conductor	Insulated Connectors	
Nest	Indenter	Size	Nest	Indenter
DV8L1	Y29PL	#8 AWG	DEV8L	Y29PLE1
DV6L	Y29PL	#6 AWG	DEV6L	Y29PLE1
DV4L	Y29PL	#4 AWG	DEV4L	Y29PLE1
DV2L	Y29PL	#2 AWG	DEV2L	Y29PLE
DV1L	Y29PL	#1 AWG	DV26L	Y29PLE
DV25L	Y29PR	1/0 AWG	DEV25L	Y29PLE
DV26L	Y29PR	2/0 AWG	DEV26L	Y29PLE



Models:

Y29BH

4.5-Ton, 6,000 PSI, Remote C-Head tool

Specifications:

Output Force: Tool Weight: Size: Die Style: Jaw Opening: **Operating Pressure:** Warranty:

4.5 Tons 5.0 lbs 10.75" x 3.00" x 1.25" D nest & Y29 series indenter dies 1.15" 6.000 PSI 5 year limited warranty

Accessories:

PT30250:

Metal carrying case (included with tool)

See Hydraulic Pumps and Hydraulic Hoses; **Pump Accessories** for other necessary equipment.



case (included with tool)

