



| REV. | DATE | REVISION DESCRIPTION | BY | CHK'D. |
|------|-------------|--|-----|--------|
| 1 | 8/27/88 | ADDED INSTALLATION DIE TABLE & NOTE G (DC 20184) | JL | KLH |
| 2 | 7/2/89 | CHGD MARKING LOCATION (REF 474) (EC) | DJD | KLH |
| 3 | 4/2/89 | ADD IND. Y34 PR & NEST B2L, 2B, 30 (DC 20208) | DJD | KH |
| 4 | 5/1/89 | ADDED MAX. CONDUCTOR SIZE TO TABLE (DC 20213) | JL | KH |
| 5 | 15 MAY 1989 | ADDED 'D' TO ALL NEST DIES (DC 20220) | MAL | KH |
| 6 | 02 JUN 1989 | ADDED 'CU/350 MCM STR. AL' TO NOTE G. DC 20225 | MAL | D.D. |
| 7 | 19 OCT 1990 | 1.10 WAS 1-1/2, 12-1/4 WAS 11-1/2 PER PCN 027. | MAL | MAL |

- NOTES:
1. OPERATING PRESSURE - 10,000 PSI.
 2. MAX FORCE GENERATED - 9 TON.
 3. HEAD AND BODY RUBBERIZED FOR BRUSH CONTACT ONLY.
 4. ACCOMODATES 'B' DIES.
 5. OVERALL DIMENSION 16 3/4"
 6. MAX. CONDUCTOR SIZE - 500 MCM STR. CU / 350 MCM STR. AL

| INSTALLATION DIES | INDENTOR | MAXIMUM CONDUCTOR SIZE | |
|-------------------|-----------|------------------------|----------|
| | | COPPER | ALUMINUM |
| B 26 D | Y34 PA | | #2 STR. |
| B 26 D | Y34 PR-5 | | #1 STR. |
| B 27 D | Y34 PR-5 | | 1/0 STR. |
| B 29 D | Y34 PR-5 | | 2/0 STR. |
| B 30 D | Y34 PR-5 | | 3/0 STR. |
| B 31 D | Y34 PR-5 | | 4/0 STR. |
| B 32 D | Y34 PR-5 | | 250 MCM |
| NO DIE REQ'D | Y34 PR-11 | | 300 MCM |
| B 26 D | | 2/0 STR | |
| B 28 D | Y34 PR | 4/0 STR | |
| B 30 D | | 300 MCM | |
| NO DIE REQ'D | | 500 MCM | |

© BURNDY CORPORATION 1988

HYPRESS

CAT. NO. Y34 BH

SCALE: FULL

DRAWN: DENALD 7/11/89

CHECKED: KLD 1/27/89

DES. APPROV: GSG 1/30/89

MFG. APPROV: [Signature]

Q.C. APPROV: [Signature]

BURNDY

DRAWING NO. SD 201515

SHT. 1 OF 2

BRUNING 4021 623162

FORM D-204-5

Sheet 2 "E" 1 size