### 15 Ton, Remote C-Head

Remote Operated Hydraulic Tool

### **Tool:** Y45

- Lifting eye
- Fully protected ram and die buttons
- Used with S dies; U dies with PT6515 adapter (sold separately)

# For Use On:

### **Tension Sleeves:**

Copper #8 sol. - 500 kcmil Aluminum #6 sol. - 954 kcmil ACSR #4 - 795 (26/7) kcmil

### Taps:

Aluminum #14 - 954 (18/1) kcmil ACSR #6 - 795 (54/7) kcmil

### Aerial Cable Connectors:

Copper #6 str. - 1500 kcmil Aluminum #4 str. - 1000 kcmil

#### HYGROUND<sup>®</sup> Compression Grounding: Copper #6 - 500 kcmil

1/2" - 1" ground rods

### Code Cable Terminals/Splices:

Copper #8 - 1500 kcmil Aluminum #8 - 1000 kcmil

### Code Cable Taps:

Copper #14 - 1000 kcmil Aluminum #14 - 900 kcmil



## Models:

Y45

Standard Remote C-Head tool

## **Specifications:**

Output Force: Tool Weight: Size: Die Style: Operating Pressure: Cycles: Warranty: 15 Tons 15.5 lbs 15.25" x 4.50" x 2.62" S and U (with PT6515) 10,000 PSI 10,000 5 year limited warranty

# Accessories:

 PT6515:
 Adapter for use with U die sets

 PT6545:
 Die carrying case for S and/or P die type dies.

 Holds eight (8) die sets. Dies sold separately.

 433206016010:
 Carry Case (included with tool)

See Hydraulic Pumps and Hydraulic Hoses; Pump Accessories for other necessary equipment.

