

**L'IL CRIMP™ 6 Ton, Latch Head**  
Hydraulic Self-Contained, Hand Operated

**Tool:** Y500CTHS

- Permanent functional D3 groove (no die needed)
- Used with W and X style dies
- 180° head rotation
- Enhanced clearance for tap connectors

**For Use On:**

Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, Compact, Stranded and Solid conductors

**Installs Splices, Taps or Terminations:**

- #8 - 600 kcmil Copper Str.
- #8 - 350 kcmil Flex
- #8 - 350 kcmil Aluminum



**Models:**

Y500CTHS      Standard Latch Head tool



**WDC4500** range taking die for  
#4 - 500 Cu Str. and  
#2 - 4/0 Cu Flex  
(sold separately)

**WDA8300** range taking die for  
#8 - 300 Al,  
#6 - 400 Cu Str. and  
#2 - 4/0 Cu Flex  
(sold separately)



**Specifications:**

**Output Force:** 6 Tons  
**Tool Weight:** 7.8 lbs  
**Size:** 18.00" x 5.50" x 2.68"  
**Die Style:** W and X  
**Warranty:** 5 year limited warranty

**Accessories:**

**WDC4500\*:** Range taking die for #4 - 500 Cu Str. and #2 - 4/0 Cu Flex  
**WDA8300\*:** Range taking die for #8 - 300 Al, #6 - 400 Cu Str. and #2 - 4/0 Cu Flex  
**PT212851:** Metal Carrying Case (included with tool)

\* When used with UL Listed/CSA Certified YA, YS, YA-A, and YS-A series terminals and splices, connections are UL/CSA. Range taking dies also for use on the YAV and YSV series.